					DEPARTMENT	TATE OF UTAH TOF NATURAL RES FOIL, GAS AND N				AMENDE	FOR		
			APPLICA	ATION FOR	PERMIT TO DRILL				1. WELL NAME and N	UMBER 5-13D-45	BTR		
2. TYPE (OF WORK	DRILL NEW WE	:u. 🙉	REENTER P	A WELL DEEPEN	WELL (3. FIELD OR WILDCA	T DUCHES	SNE		
4. TYPE C	OF WELL		Oil Well		ed Methane Well: NO				5. UNIT or COMMUNI	TIZATION A	GREEME	NT NAM	E
6. NAME	OF OPERATO	R	On Wen	BILL BARR					7. OPERATOR PHONE	303 312-	8164		
8. ADDRE	SS OF OPERA		1099 18th \$		00, Denver, CO, 80202				9. OPERATOR E-MAII			om	
	RAL LEASE NU L, INDIAN, OR	STATE)			11. MINERAL OWNERS	HIP	_	FEE (12. SURFACE OWNER FEDERAL INI	SHIP DIAN (📵)	STATE () FE	E ()
13. NAMI	OF SURFAC	20G0005608 E OWNER (if box	12 = 'fee')	1	TESEIVE W	### OH 12 (14. SURFACE OWNER		7		
15. ADDF	RESS OF SURF	FACE OWNER (if I	box 12 = 'fe	ee')					16. SURFACE OWNE	R E-MAIL (i	f box 12 :	= 'fee')	
		OR TRIBE NAME			18. INTEND TO COMM		N FRO	M	19. SLANT				
(if box 1	2 = 'INDIAN')	Uintah and Ouray				ommingling Applica	tion)	NO 📵	VERTICAL DIF	RECTIONAL	📵 но	ORIZONT.	AL 🔵
20. LOC	ATION OF WE	LL		F	OOTAGES	QTR-QTR		SECTION	TOWNSHIP	RAN	IGE	МЕ	RIDIAN
LOCATI	ON AT SURFA	CE		2079 F	NL 868 FWL	SWNW		13	4.0 S	5.0	W		U
Top of U	Jppermost Pr	oducing Zone		1981 F	NL 810 FWL	SWNW		13	4.0 S	5.0	W		U
At Tota				1980 F	NL 810 FWL	SWNW		13	4.0 S	5.0			U
21. COUI	NTY	DUCHESNE			22. DISTANCE TO NEA	810			23. NUMBER OF ACR	640			
					25. DISTANCE TO NEA (Applied For Drilling of		E POO	L	26. PROPOSED DEPT		VD: 9218		
27. ELEV	ATION - GRO	JND LEVEL 6223			28. BOND NUMBER	LPM8874725			29. SOURCE OF DRIL WATER RIGHTS APPR		BER IF AP	PLICABL	.E
Cárin a	Uala Siza	Casing Siza	Lange	h Waint		and Cement Inf		tion	Cement		Caalsa	Viola	Mainht
String	Hole Size	Casing Size	Lengt			Max Mud Wt.	+		No Used		Sacks 0	Yield 0.0	Weight 0.0
Surf	12.25	9.625	0 - 24			8.8	_	Halliburto	n Light , Type Unkr	nown	340	3.16	11.0
								Halliburton	Premium , Type Un	known	210	1.36	14.8
Prod	8.75	5.5	0 - 92	20 17.0	P-110 LT&C	9.6	-		Unknown		630 950	2.31 1.42	11.0
									OTIKITOWIT		930	1.42	13.3
					A`	TTACHMENTS							
	VE	ERIFY THE FOL	LOWING	ARE ATTA	CHED IN ACCORDAN	CE WITH THE UT	AH OI	IL AND GAS	CONSERVATION G	ENERAL	RULES		
I ✓ v	VELL PLAT OR	MAP PREPARED	BY LICENS	SED SURVEYO	DR OR ENGINEER	✓ cor	MPLETI	E DRILLING P	LAN				
AI	FFIDAVIT OF S	TATUS OF SURFA	CE OWNE	R AGREEMEI	NT (IF FEE SURFACE)	FOR	M 5. IF	OPERATOR I	S OTHER THAN THE LI	EASE OWN	ER		
I ✓ DI	RECTIONAL S	URVEY PLAN (IF	DIRECTIO	NALLY OR H	ORIZONTALLY DRILLED	тор	OGRAF	PHICAL MAP					
NAME V	enessa Langm	acher		ТІТ	LE Senior Permit Analyst			PHONE 303	312-8172				
SIGNAT	URE			DA	TE 05/23/2012			EMAIL vlang	macher@billbarrettcorp	p.com			
	iber assigne 01351440			АР	PROVAL			Bol	egill				
								Permi	t Manager				

BILL BARRETT CORPORATION <u>DRILLING PLAN</u>

5-13D-45 BTR

SW NW, 2079' FNL and 868' FWL, Section 13, T4S-R5W, USB&M (surface hole) SW NW, 1980' FNL and 810' FWL, Section 13, T4S-R5W, USB&M (bottom hole) Duchesne County, Utah

1 - 2. <u>Estimated Tops of Geological Markers and Formations Expected to Contain Water, Oil and Gas and Other Minerals</u>

Formation	Depth – MD	Depth - TVD
Lower Green River*	4,559'	4,558'
Douglas Creek	5,414'	5,413'
Black Shale	6,209'	6,208'
Castle Peak	6,474'	6,473'
Uteland Butte	6,824'	6,823'
Wasatch*	7,069'	7,068'
TD	9,220'	9,218'

*PROSPECTIVE PAY

To operate most efficiently in this manner.

The Wasatch and the Lower Green River are primary objectives for oil/gas.

Base of Useable Water = 5,500'

3. BOP and Pressure Containment Data

Depth Intervals	BOP Equipment
0-2,400	No pressure control required
2,400' – TD	11" 5000# Ram Type BOP
	11" 5000# Annular BOP
- Drilling spool to a	accommodate choke and kill lines;
- Ancillary equipme	ent and choke manifold rated at 5,000 psi. All BOP and BOPE tests will be in
accordance with the	he requirements of onshore Order No. 2;
- The BLM and the	State of Utah Division of Oil, Gas and Mining will be notified 24 hours in
advance of all BO	OP pressure tests.
- BOP hand wheels	may be underneath the sub-structure of the rig if the drilling rig used is set up

4. <u>Casing Program</u>

Hole Size	SETTING DEPTH		Casing	Casing	Casing		
	(FROM)	<u>(TO)</u>	Size	Weight	<u>Grade</u>	Thread	Condition
26"	Surface	80'	16"	65#			
12 1/4"	Surface	2,400'	9 5/8"	36#	J or K 55	ST&C	New
8 3/4"	Surface	TD	5 ½"	17#	P-110	LT&C	New

RECEIVED: May 23, 2012

Bill Barrett Corporation Drilling Program 5-13D-45 BTR Duchesne County, Utah

5. <u>Cementing Program</u>

16" Conductor Casing	Grout
9 5/8" Surface Casing	Lead: 340 sx Halliburton Light Premium with additives
	mixed at 11.0 ppg (yield = $3.16 \text{ ft}^3/\text{sx}$) circulated to surface
	with 75% excess. TOC @ Surface
	Tail: 210 sx Halliburton Premium Plus cement with
	additives mixed at 14.8 ppg (yield = $1.36 \text{ ft}^3/\text{sx}$), calculated
	hole volume with 75% excess. TOC @ 1,900'
5 ½" Production Casing	Lead: 630 sx Tuned Light cement with additives mixed at
	11.0 ppg (yield = $2.31 \text{ ft}^3/\text{sx}$). TOC @ 1,900'
	Tail: 950 sx Halliburton Econocem cement with additives
	mixed at 13.5 ppg (yield = $1.42 \text{ ft}^3/\text{sx}$). Top of cement to
	be determined by log and sample evaluation; estimated TOC
	@ 5,709'

6. <u>Mud Program</u>

<u>Interval</u>	<u>Weight</u>	Viscosity	Fluid Loss (API filtrate)	<u>Remarks</u>
0'-80'	8.3 - 8.8	26 – 36	NC	Freshwater Spud Mud Fluid System
80' - 2,400'	8.3 – 8.8	26 – 36	NC	Freshwater Spud Mud Fluid System
2,400' – TD	8.6 – 9.6	42-52	20 cc or less	DAP Polymer Fluid System

Note: Sufficient mud materials to maintain mud properties, control lost circulation and to contain "kicks" will be available at wellsite. BBC may require minor amounts of diesel to be added to its fluid system in order to reduce torque and drag.

7. Testing, Logging and Core Programs

Cores	None anticipated;
Testing	None anticipated; drill stem tests may be run on shows of interest;
Sampling	30' to 50' samples; surface casing to TD. Preserve samples all show intervals;
Surveys	MWD as needed to land wellbore;
Logging	DIL-GR-SP, FDC-CNL-GR-CALIPER-Pe-Microlog, Sonic-GR (all TD to surface).
	FMI & Sonic Scanner to be run at geologist's discretion.

8. <u>Anticipated Abnormal Pressures or Temperatures</u>

No abnormal pressures or temperatures or other hazards are anticipated.

Maximum anticipated bottom hole pressure equals approximately 4602 psi* and maximum anticipated surface pressure equals approximately 2574 psi** (bottom hole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

^{*}Max Mud Wt x 0.052 x TD = A (bottom hole pressure)

^{**}Maximum surface pressure = A - (0.22 x TD)

Bill Barrett Corporation Drilling Program 5-13D-45 BTR Duchesne County, Utah

9. Auxiliary Equipment

- a) Upper kelly cock; lower Kelly cock will be installed while drilling
- b) Inside BOP or stab-in valve (available on rig floor)
- c) Safety valve(s) and subs to fit all string connections in use Mud monitoring will be visually observed

10. Location and Type of Water Supply

Water for the drilling and completion will be trucked from the Duchesne City Culinary Water Dock located in Sec. 1, T4S, R5W water right number 43-180.

11. <u>Drilling Schedule</u>


Location Construction: November 2013
Spud: November 2013
Duration: 15 days drilling time
45 days completion time


RECEIVED: May 23, 2012



LAKE CANYON & BLACK TAIL RIDGE CEMENT VOLUMES

Well Name: <u>5-13D-45 BTR</u>





5-13D-45 BTR Proposed Cementing Program


Job Recommendation		Sur	face Casing
Lead Cement - (1900' - 0')			
Halliburton Light Premium	Fluid Weight:	11.0	lbm/gal
5.0 lbm/sk Silicalite Compacted	Slurry Yield:	3.16	ft ³ /sk
0.25 lbm/sk Kwik Seal	Total Mixing Fluid:	19.48	Gal/sk
0.125 lbm/sk Poly-E-Flake	Top of Fluid:	0'	
2.0% Bentonite	Calculated Fill:	1,900'	
	Volume:	185.46	bbl
	Proposed Sacks:	340	sks
Tail Cement - (TD - 1900')			
Premium Cement	Fluid Weight:	14.8	lbm/gal
2.0% Calcium Chloride	Slurry Yield:	1.36	ft ³ /sk
	Total Mixing Fluid:	6.37	Gal/sk
	Top of Fluid:	1,900'	
	Calculated Fill:	500'	
	Volume:	48.80	bbl
	Proposed Sacks:	210	sks


Job Recommendation		Produc	tion Casing
Lead Cement - (5709' - 1900')			
Tuned Light TM System	Fluid Weight:	11.0	lbm/gal
	Slurry Yield:	2.31	ft ³ /sk
	Total Mixing Fluid:	10.65	Gal/sk
	Top of Fluid:	1,900'	
	Calculated Fill:	3,809'	
	Volume:	257.02	bbl
	Proposed Sacks:	630	sks
Tail Cement - (9220' - 5709')			
Econocem TM System	Fluid Weight:	13.5	lbm/gal
0.125 lbm/sk Poly-E-Flake	Slurry Yield:	1.42	ft ³ /sk
1.0 lbm/sk Granulite TR 1/4	Total Mixing Fluid:		Gal/sk
	Top of Fluid:	5,709'	
	Calculated Fill:	3,511'	
	Volume:		bbl
	Proposed Sacks:	950	sks


RECEIVED: May 23, 2012


RECEIVED:

Мау









43013514460000 Number:



COMPANY DETAILS: BILL BARRETT CORP

Calculation Method: Minimum Curvature

Error System: ISCWSA Scan Method: Closest Approach 3D

Error Surface: Elliptical Conic

Warning Method: Error Ratio

5-13D-45 BTR 3PT MKR 5798.0

5-13D-45 BTR PBHL

SITE DETAILS: 5-13D-45 BTR Blacktail Ridge

Site Latitude: 40° 8' 5.240 N Site Longitude: 110° 24' 15.548 W

Positional Uncertainity: 0.0 Convergence: 0.70 Local North: True

WELL DETAILS: 5-13D-45 BTR

Ground Level: 6223.0

+E/-W Northing Easting +N/-S Latittude Longitude Slot 0.0 658018.50 40° 8' 5.240 N 110° 24' 15.548 W 0.0 2306338.47

WELLBORE TARGET DETAILS (LAT/LONG) +E/-W +N/-S Latitude Longitude Shape 110° 24' 16.301 W 110° 24' 16.301 W Rectangle (Sides: L200.0 W200.0) 98.0 -58.4 40° 8' 6.209 N Rectangle (Sides: L200.0 W200.0) -58.4 40° 8' 6.209 N 98.0


	SECTION DETAILS										
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target	
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0		
2	2300.0	0.00	0.00	2300.0	0.0	0.0	0.00	0.00	0.0		
3	2429.3	1.94 3	329.19	2429.3	1.9	-1.1	1.50	329.19	2.2		
4	5670.6	1.94 3	329.19	5668.7	96.1	-57.3	0.00	0.00	111.9		
5	5799.9	0.00	0.00	5798.0	98.0	-58.4	1.50	180.00	114.1	5-13D-45 BTR 3PT MKR	
6	9219.9	0.00	0.00	9218.0	98.0	-58.4	0.00	0.00	114.1	5-13D-45 BTR PBHL	


CASING DETAILS

TVD

9218.0

No casing data is available





Т Azimuths to True North Magnetic North: 11.36°

Magnetic Field Strength: 52180.7snT Dip Angle: 65.78° Date: 4/18/2012

FORMATION TOP DETAILS

Formation

Mahogany TGR3

3PT MKR

CR 1

CR 2 CR 3 CR 4

CR 4A

CR 5

CR₆

CR 7

Wasatch

Green River

Douglas Creek

Castle Peak Uteland Butte

Black Shale Facies

MDPath

2558.1

3203.5 4559.2

5414.7

5799.9

6209.9

6474.9 6824.9

6884.9

7214.9

7474.9

7784.9

8054.9

8194.9

8374.9

8919.9

TVDPath

2558.0

3203.0 4558 0 5413.0

5798.0

6208.0

6473.0 6823.0

6883.0

7068.0

7213.0 7473.0 7783.0

8053.0

8193.0

8373.0

8918.0

Model: IGRF2010

BILL BARRETT CORP

DUCHESNE COUNTY, UT (NAD 27) 5-13D-45 BTR 5-13D-45 BTR

5-13D-45 BTR

Plan: Design #1

Standard Planning Report

18 April, 2012

Planning Report

Compass Database:

Project:

Company: **BILL BARRETT CORP**

Site: 5-13D-45 BTR Well: 5-13D-45 BTR 5-13D-45 BTR

DUCHESNE COUNTY, UT (NAD 27)

0.0 ft

IGRF2010

Wellbore: Design #1 Design:

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well 5-13D-45 BTR

KB @ 6239.0ft (Original Well Elev) KB @ 6239.0ft (Original Well Elev)

40° 8' 5.240 N

6,223.0 ft

110° 24' 15.548 W

52,181

(nT)

True

Minimum Curvature

Project DUCHESNE COUNTY, UT (NAD 27)

US State Plane 1927 (Exact solution) Map System:

NAD 1927 (NADCON CONUS) Geo Datum:

Utah Central 4302 Map Zone:

System Datum:

Ground Level

Ground Level:

65.78

(°)

5-13D-45 BTR Site

Position Uncertainty

Northing: 658,018.51 ft Site Position: Latitude: 40° 8' 5.240 N From: Lat/Long Easting: 2,306,338.47 ft Longitude: 110° 24' 15.548 W **Position Uncertainty:** 0.0 ft Slot Radius: **Grid Convergence:** 0.70 °

Well 5-13D-45 BTR **Well Position** +N/-S 0.0 ft Northing: 658,018.50 ft Latitude: +E/-W 0.0 ft Easting: 2,306,338.47 ft Longitude:

Wellhead Elevation:

4/18/2012

Wellbore 5-13D-45 BTR Magnetics **Model Name** Sample Date Declination **Dip Angle** Field Strength

(°)

11.36

ft

Design #1 Design **Audit Notes:** Tie On Depth: Version: Phase: PLAN 0.0 Vertical Section: Depth From (TVD) +N/-S +E/-W Direction (ft) (ft) (ft) (°) 0.0 329.19 0.0 0.0

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,429.3	1.94	329.19	2,429.3	1.9	-1.1	1.50	1.50	0.00	329.19	
5,670.6	1.94	329.19	5,668.7	96.1	-57.3	0.00	0.00	0.00	0.00	
5,799.9	0.00	0.00	5,798.0	98.0	-58.4	1.50	-1.50	0.00	180.00	5-13D-45 BTR 3PT N
9,219.9	0.00	0.00	9,218.0	98.0	-58.4	0.00	0.00	0.00	0.00	5-13D-45 BTR PBHL

Planning Report

Database: Compass

Company: BILL BARRETT CORP

 Project:
 DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-13D-45 BTR

 Well:
 5-13D-45 BTR

 Well:
 5-13D-45 BTR

 Wellbore:
 5-13D-45 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 5-13D-45 BTR

KB @ 6239.0ft (Original Well Elev) KB @ 6239.0ft (Original Well Elev)

True

Minimum Curvature

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
						` '	, ,	, ,	, ,
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1.500.0	0.00	0.00	1.500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0				0.00	0.00
					0.0	0.0	0.00		
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	1.50	329.19	2,400.0	1.1	-0.7	1.3	1.50	1.50	0.00
2,400.0	1.00	020.10	2,400.0		0.7	1.0	1.00	1.00	0.00
2,429.3	1.94	329.19	2,429.3	1.9	-1.1	2.2	1.50	1.50	0.00
2,500.0	1.94	329.19	2,499.9	3.9	-2.3	4.6	0.00	0.00	0.00
2,558.1	1.94	329.19	2,558.0	5.6	-3.4	6.5	0.00	0.00	0.00
	1.54	323.13	2,000.0	5.0	-0	0.5	0.00	0.00	0.00
Green River									
2,600.0	1.94	329.19	2,599.9	6.8	-4.1	8.0	0.00	0.00	0.00
2,700.0	1.94	329.19	2,699.8	9.7	-5.8	11.4	0.00	0.00	0.00
2,800.0	1.94	329.19	2,799.8	12.7	-7.5	14.7	0.00	0.00	0.00
2,900.0	1.94	329.19	2,899.7	15.6	-9.3	18.1	0.00	0.00	0.00
3,000.0	1.94	329.19	2,999.6	18.5	-11.0	21.5	0.00	0.00	0.00
3,100.0	1.94	329.19	3,099.6	21.4	-12.7	24.9	0.00	0.00	0.00
3,200.0	1.94	329.19	3,199.5	24.3	-14.5	28.3	0.00	0.00	0.00
3,200.0	1.34	528.18	٥, ١٥٥.٥	24.0	-14.5	20.5	0.00	0.00	0.00
3,203.5	1.94	329.19	3,203.0	24.4	-14.5	28.4	0.00	0.00	0.00
Mahogany			,		_				
	4.04	200.40	0.000 5	07.0	40.0	04.7	0.00	0.00	0.00
3,300.0	1.94	329.19	3,299.5	27.2	-16.2	31.7	0.00	0.00	0.00
3,400.0	1.94	329.19	3,399.4	30.1	-17.9	35.0	0.00	0.00	0.00
3,500.0	1.94	329.19	3,499.4	33.0	-19.7	38.4	0.00	0.00	0.00
3,600.0	1.94	329.19	3,599.3	35.9	-21.4	41.8	0.00	0.00	0.00
3,700.0	1.94	329.19	3,699.2	38.8	-23.2	45.2	0.00	0.00	0.00
3,800.0	1.94	329.19	3,799.2	41.7	-24.9	48.6	0.00	0.00	0.00
3,900.0	1.94	329.19	3,899.1	44.6	-26.6	52.0	0.00	0.00	0.00
4,000.0	1.94	329.19	3,999.1	47.5	-28.4	55.4	0.00	0.00	0.00
4,100.0	1.94	329.19	4,099.0	50.5	-30.1	58.7	0.00	0.00	0.00
4,200.0	1.94	329.19	4.199.0	53.4	-31.8	62.1	0.00	0.00	0.00
	1.94		,				0.00		0.00
4,300.0		329.19	4,298.9	56.3	-33.6	65.5		0.00	
4,400.0	1.94	329.19	4,398.8	59.2	-35.3	68.9	0.00	0.00	0.00
4,500.0	1.94	329.19	4,498.8	62.1	-37.0	72.3	0.00	0.00	0.00
4,559.2	1.94	329.19	4,558.0	63.8	-38.0	74.3	0.00	0.00	0.00
TGR3									

Planning Report

Database: Compass

Company: BILL BARRETT CORP

Project: DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-13D-45 BTR

 Well:
 5-13D-45 BTR

 Wellbore:
 5-13D-45 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well 5-13D-45 BTR

KB @ 6239.0ft (Original Well Elev) KB @ 6239.0ft (Original Well Elev)

True

Minimum Curvature

esign:	Design #1								
Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,600.0 4,700.0 4,800.0 4,900.0	1.94 1.94 1.94 1.94	329.19 329.19 329.19 329.19	4,598.7 4,698.7 4,798.6 4,898.6	65.0 67.9 70.8 73.7	-38.8 -40.5 -42.2 -44.0	75.7 79.1 82.4 85.8	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
5,000.0 5,100.0 5,200.0 5,300.0 5,400.0	1.94 1.94 1.94 1.94 1.94	329.19 329.19 329.19 329.19 329.19	4,998.5 5,098.4 5,198.4 5,298.3 5,398.3	76.6 79.5 82.4 85.3 88.2	-45.7 -47.4 -49.2 -50.9 -52.6	89.2 92.6 96.0 99.4 102.7	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00
5,414.7 Douglas Cree	1.94	329.19	5,413.0	88.7	-52.9	103.2	0.00	0.00	0.00
5,500.0 5,600.0 5,670.6 5,700.0 5,799.9	1.94 1.94 1.94 1.50 0.00	329.19 329.19 329.19 329.19 0.00	5,498.2 5,598.2 5,668.7 5,698.1 5,798.0	91.2 94.1 96.1 96.9 98.0	-54.4 -56.1 -57.3 -57.8 -58.4	106.1 109.5 111.9 112.8 114.1	0.00 0.00 0.00 1.50 1.50	0.00 0.00 0.00 -1.50 -1.50	0.00 0.00 0.00 0.00 30.84
3PT MKR			2,12212						
5,800.0 5,900.0 6,000.0 6,100.0	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	5,798.1 5,898.1 5,998.1 6,098.1	98.0 98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1 114.1	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
6,200.0 6,209.9	0.00	0.00 0.00	6,198.1 6,208.0	98.0 98.0	-58.4 -58.4	114.1 114.1	0.00	0.00	0.00 0.00
Black Shale F		0.00	0,200.0	00.0	00.1	111.1	0.00	0.00	0.00
6,300.0 6,400.0 6,474.9	0.00 0.00 0.00	0.00 0.00 0.00	6,298.1 6,398.1 6,473.0	98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
Castle Peak	0.00	0.00	0.400.4	00.0	50.4	4444	0.00	0.00	0.00
6,500.0 6,600.0 6,700.0 6,800.0 6,824.9	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	6,498.1 6,598.1 6,698.1 6,798.1 6,823.0	98.0 98.0 98.0 98.0 98.0	-58.4 -58.4 -58.4 -58.4 -58.4	114.1 114.1 114.1 114.1 114.1	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00
Uteland Butte 6,884.9	0.00	0.00	6,883.0	98.0	-58.4	114.1	0.00	0.00	0.00
CR 1									
6,900.0 7,000.0 7,069.9	0.00 0.00 0.00	0.00 0.00 0.00	6,898.1 6,998.1 7,068.0	98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
Wasatch 7,100.0 7,200.0	0.00 0.00	0.00 0.00	7,098.1 7,198.1	98.0 98.0	-58.4 -58.4	114.1 114.1	0.00 0.00	0.00 0.00	0.00 0.00
7,214.9	0.00	0.00	7,213.0	98.0	-58.4	114.1	0.00	0.00	0.00
CR 2 7,300.0 7,400.0 7,474.9	0.00 0.00 0.00	0.00 0.00 0.00	7,298.1 7,398.1 7,473.0	98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
CR 3 7,500.0	0.00	0.00	7,498.1	98.0	-58.4	114.1	0.00	0.00	0.00
7,600.0 7,700.0 7,784.9 CR 4	0.00 0.00 0.00	0.00 0.00 0.00	7,598.1 7,698.1 7,783.0	98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00

Planning Report

Database: Compass

Company: BILL BARRETT CORP

Project: DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-13D-45 BTR

 Well:
 5-13D-45 BTR

 Wellbore:
 5-13D-45 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 5-13D-45 BTR

KB @ 6239.0ft (Original Well Elev) KB @ 6239.0ft (Original Well Elev)

True

Minimum Curvature

anned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
7,800.0 7,900.0	0.00 0.00	0.00 0.00	7,798.1 7,898.1	98.0 98.0	-58.4 -58.4	114.1 114.1	0.00 0.00	0.00 0.00	0.00 0.00
8,000.0 8,054.9	0.00 0.00	0.00 0.00	7,998.1 8,053.0	98.0 98.0	-58.4 -58.4	114.1 114.1	0.00 0.00	0.00 0.00	0.00 0.00
CR 4A 8,100.0 8,194.9	0.00 0.00	0.00 0.00	8,098.1 8,193.0	98.0 98.0	-58.4 -58.4	114.1 114.1	0.00 0.00	0.00 0.00	0.00 0.00
CR 5 8,200.0	0.00	0.00	8,198.1	98.0	-58.4	114.1	0.00	0.00	0.00
8,300.0 8,374.9	0.00 0.00	0.00 0.00	8,298.1 8,373.0	98.0 98.0	-58.4 -58.4	114.1 114.1	0.00 0.00	0.00 0.00	0.00 0.00
CR 6									
8,400.0 8,500.0 8,600.0	0.00 0.00 0.00	0.00 0.00 0.00	8,398.1 8,498.1 8,598.1	98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
8,700.0 8,800.0 8,900.0 8,919.9	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	8,698.1 8,798.1 8,898.1 8,918.0	98.0 98.0 98.0 98.0	-58.4 -58.4 -58.4 -58.4	114.1 114.1 114.1 114.1	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
CR 7									
9,000.0	0.00	0.00	8,998.1	98.0	-58.4	114.1	0.00	0.00	0.00
9,100.0 9,200.0 9,219.9	0.00 0.00 0.00	0.00 0.00 0.00	9,098.1 9,198.1 9,218.0	98.0 98.0 98.0	-58.4 -58.4 -58.4	114.1 114.1 114.1	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00

Formations						
	Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
	2,558.1	2,558.0	Green River		0.00	
	3,203.5	3,203.0	Mahogany		0.00	
	4,559.2	4,558.0	TGR3		0.00	
	5,414.7	5,413.0	Douglas Creek		0.00	
	5,799.9	5,798.0	3PT MKR		0.00	
	6,209.9	6,208.0	Black Shale Facies		0.00	
	6,474.9	6,473.0	Castle Peak		0.00	
	6,824.9	6,823.0	Uteland Butte		0.00	
	6,884.9	6,883.0	CR 1		0.00	
	7,069.9	7,068.0	Wasatch		0.00	
	7,214.9	7,213.0	CR 2		0.00	
	7,474.9	7,473.0	CR 3		0.00	
	7,784.9	7,783.0	CR 4		0.00	
	8,054.9	8,053.0	CR 4A		0.00	
	8,194.9	8,193.0	CR 5		0.00	
	8,374.9	8,373.0	CR 6		0.00	
	8,919.9	8,918.0	CR 7		0.00	

SURFACE USE PLAN

BILL BARRETT CORPORATION 5-13D-45 BTR Pad

SW NW, 2079' FNL and 868' FWL, Sec. 13, T4S-R5W (surface hole) SW NW, 1980' FNL and 810' FWL, Sec. 13, T4S-R5W (bottom hole) Duchesne County, Utah

The onsite inspection for this pad occurred on February 1, 2012. This is a new pad with one proposed well. Plat changes and site specific stipulations requested at the onsite are reflected within this APD and summarized below.

- a) Has arch re-route for access and pipeline corridors deviating from the existing two-track road;
- b) Relocated topsoil from corners 1 & 2 area to corner 3 area and corner 6 area to maximize interim reclamation and minimize topsoil loss;
- c) Round pad corner 8 by 8 feet to minimize cut and fill slopes;

The excavation contractor would be provided with an approved copy of the surface use plan of operations before initiating construction.

1. <u>Existing Roads:</u>

- a. The proposed well site is located approximately 5.8 miles south of Duchesne, Utah. Maps and directions reflecting the route to the proposed well site are included (see Topographic maps A and B).
- b. The existing State maintained Highway 191 would be utilized from Duchesne for 2.3 miles to the existing Duchesne County maintained Sowers Canyon Road. The Sowers Canyon Road would be utilized for 1.8 miles to the planned new access road.
- c. Project roads would require routine year-round maintenance to provide year-round access. Maintenance would include inspections, reduction of ruts and holes, maintenance to keep water off the road, replacement of surfacing materials, and clearing of sediment blocking ditches and culverts. Should snow removal become necessary, roads would be cleared with a motor grader and snow would be stored along the down gradient side to prohibit runoff onto the road. Aggregate would be used as necessary to maintain a solid running surface and minimize dust generation.
- d. Vehicle operators would obey posted speed restrictions and observe safe speeds commensurate with road and weather conditions. Travel would be limited to the existing access roads and proposed access road.
- e. The use of roads under Utah State and Duchesne County maintenance are necessary to access the project area with no improvements proposed. No encroachment or pipeline crossing permits are required.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

f. All existing roads would be maintained and kept in good repair during all phases of operation.

2. Planned Access Road:

- a. Approximately 7,014 feet of new access road is planned from the proposed 16-13D-45 BTR access road. The proposed 16-13D-45 BTR access road continues an additional 1,893 feet to the existing Sowers Canyon access road (see Topographic Map B). The proposed access road crosses entirely Ute Tribe surface.
- b. The planned access road would be constructed to a 30-foot ROW width with an 18-foot travel surface. See section 12.d. below for disturbance estimates.
- c. New road construction and improvements of existing roads would typically require the use of motor graders, crawler tractors, 10-yard end dump trucks, and water trucks. The standard methodology for building new roads involves the use of a crawler tractor or track hoe to windrow the vegetation to one side of the road corridor, remove topsoil to the opposing side of the corridor, and rough-in the roadway. This is followed by a grader or bulldozer to establish barrow ditches and crown the road surface. Where culverts are required, a track hoe or backhoe would trench the road and install the culverts. Some hand labor would be required when installing and armoring culverts. Road base or gravel in some instances would be necessary and would be hauled in and a grader used to smooth the running surface.
- d. The proposed road would be constructed to facilitate drainage, control erosion and minimize visual impacts by following natural contours where practical. No unnecessary side-casting of material would occur on steep slopes.
- e. A maximum grade of 10% would be maintained throughout the project with minimum cuts and fills, as necessary, to access the well.
- f. Excess rock from construction of the pad may be used for surfacing of the access road if necessary. Any additional aggregate necessary would be obtained from private or State of Utah lands in conformance with applicable regulations. Aggregate would be of sufficient size, type, and amount to allow all weather access and alleviate dust.
- g. Where topsoil removal is necessary, it would be windrowed (i.e. stockpiled/accumulated along the edge of the ROW and in a low row/pile parallel with the ROW) and re-spread over the disturbed area after construction and backfilling are completed. Vegetation removed from the disturbed area would also be re-spread to provide protection, nutrient recycling, and a seed source for reclamation.
- h. Turnouts are not proposed.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

- i. No culverts and no low-water crossings are anticipated. Adequate drainage structures, where necessary, would be incorporated into the remainder of the road to prevent soil erosion and accommodate all-weather traffic.
- j. No gates or cattle guards are anticipated at this time.
- k. Surface disturbance and vehicular travel would be limited to the approved location access road. Adequate signs would be posted, as necessary, to warn the public of project related traffic.
- All access roads and surface disturbing activities would conform to the
 appropriate standard, **no higher than necessary**, to accommodate their intended
 function adequately as outlined in the Bureau of Land Management and Forest
 Service publication: <u>Surface Operating Standards for Oil and Gas Exploration</u>
 and Development, Fourth Edition Revised 2007.
- m. The operator would be responsible for all maintenance needs of the new access road.

3. Location of Existing Wells (see One-Mile Radius Map):

a. Following is a list of wells with surface hole locations within a one-mile radius of the proposed pad:

i.	water wells	none
ii.	injection wells	none
iii.	disposal wells	none
iv.	drilling wells	none
v.	temp shut-in wells	none
vi.	producing wells	one
	abandoned wells	three

4. <u>Location of Production Facilities</u>

- a. Surface facilities would consist of a wellhead, separator, gas meter, combustor, (1) 500 gal methanol tank, (1) 500 glycol tank, (3) 500 bbl oil tanks, (1) 500 bbl water tank, (1) 500 bbl test tank, (1) 1000 gal propane tank, a pumping unit or Roto-flex unit or ESP or gas lift unit, electrical or with a natural gas or diesel fired motor, solar panels, solar chemical and methanol pumps and one trace pump. See attached proposed facility diagram.
- b. Most wells would be fitted with a pump jack or Roto-flex unit or ESP or gas lift to assist liquid production. The prime mover for pump jacks or Roto-flex units would be small (100 horsepower or less), electric motor or natural gas or diesel fired internal combustion engines. If a gas lift is installed, it would be set on a 10 ft x 25 ft pad and the prime mover would be a natural gas-fired internal

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

combustion engine rated at 200 horsepower or less or an electric compressor of similar horsepower powered by electricity.

- c. The tank battery would be surrounded by a secondary containment berm of sufficient capacity to contain 1.1 times the entire capacity of the largest single tank and sufficient freeboard to contain precipitation. All loading lines and valves would be placed inside the berm surrounding the tank battery or would utilize catchment basins to contain spills. All liquid hydrocarbon production and measurement shall conform to the provisions of 43 CFR 3162.7-2 and Onshore Oil and Gas Order No. 4 for the measurement of oil.
- d. Gas meter run(s) would be constructed and located on lease within 500 feet of the wellheads. Meter runs would be housed and/or fenced. As practicably feasible, meters would be equipped with remote telemetry monitoring systems. All gas production and measurement shall comply with the provisions of 43 CFR 3162.7-3, Onshore Oil and Gas Order No. 5, and American Gas Association (AGA) Report No. 3.
- e. A combustor may be installed at this location for control of associated condensate tank emissions. A combustor ranges from 24 inches to 48 inches wide and is approximately 27 ft tall. Combustor placement would be on existing disturbance.
- f. Approximately 7,096 feet of pipeline corridor containing up to three lines (one gas pipeline up to 8 inch in diameter, one water line up to 4 inch in diameter and one residue line up to 4 inch in diameter) is proposed traversing east then south to the proposed 16-13D-45 BTR pipeline corridor. The proposed 16-13D-45 BTR pipeline corridor continues an additional 11,082 feet south then west to an existing BBC maintained pipeline corridor (see Topographic Map C). Pipelines would be constructed of steel, polyethylene or fiberglass and would connect to the proposed pipeline servicing nearby BBC wells. The pipeline crosses entirely Ute Tribe surface.
- g. The new segment of gas pipeline would be surface laid or buried within a 30 foot wide pipeline corridor adjacent to the proposed access road. Approval to bury the lines would be obtained from the surface owner(s). See 12.d below for disturbance estimates.
- h. Construction of the ROW would temporarily utilize the 30 foot disturbed width for the road for a total disturbed width of 60 foot for the road and pipeline corridors. The use of the proposed well site and access roads would facilitate the staging of the pipeline construction.
- Pipeline construction methods and practices would be planned and conducted by BBC with the objective of enhancing reclamation and fostering the reestablishment of the native plant community.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

- j. All permanent above-ground structures would be painted a flat, non-reflective color, such as Beetle Green, to match the standard environmental colors. All facilities would be painted the designated color at the time of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) may be excluded.
- k. Site security guidelines identified in 43 CFR 3162.7-5 and Onshore Oil and Gas Order No. 3 would be adhered to. Any modifications to proposed facilities would be reflected in the site security diagram submitted.
- 1. The site would require periodic maintenance to ensure that drainages are kept open and free of debris, and that surfaces are properly treated to reduce erosion, fugitive dust, and impacts to adjacent areas.

5. <u>Location and Type of Water Supply:</u>

a. Water for the drilling and completion would be trucked from any of the following locations:

Water Right No. and				Point of	
Application or Change No.	Applicant	Allocation	Date	Diversion	Source
43-180	Duchesne City	5 cfs	8/13/2004	Knight	Duchesne
	Water Service			Diversion Dam	River
	District				
43-1202, Change a13837	Myton City	5.49 cfr and	3/21/1986	Knight	Duchesne
		3967 acre feet		Diversion Dam	River
43-10444, Appln A57477	Duchesne	2 cfs	1994	Ditch at	Cow Canyon
	County Upper			Source	Spring
	Country Water				
43-10446, Appln F57432	Duchesne	1.58 cfs	1994	Ditch at	Cow Canyon
	County Upper			Source	Spring
	Country Water				
43-1273, Appln A17462	J.J.N.P.	7 cfs	1946	Strawberry	Strawberry
	Company			River	River
43-1273, Appln t36590	J.J.N.P.	4 cfs	6/03/2010	Strawberry	Strawberry
	Company			River	River
43-2505, Appln t37379	McKinnon	1.3 cfs	4/28/2011	Pumped from	Water Canyon
	Ranch			Sec, 17,	Lake
	Properties, LC			T4SR6W	
43-12415, Change A17215a	Peatross	1.89 cfs	09/2011	Dugout Pond	Strawberry
	Ranch, LLC				River

b. No new water well is proposed with this application.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

- c. Should additional water sources be pursued they would be properly permitted through the State of Utah Division of Water Rights.
- d. Water use would vary in accordance with the formations to be drilled but would be up to approximately 5.41 acre feet for drilling and completion operations.

6. Source of Construction Material:

- a. The use of materials would conform to 43 CFR 3610.2-3.
- b. No construction materials would be removed from the lease or EDA area.
- c. If any additional gravel is required, it would be obtained from a local supplier having a permitted source of materials within the general area.

7. Methods of Handling Waste Disposal:

- a. All wastes associated with this application would be contained and disposed of utilizing approved facilities.
- b. The reserve pit would be constructed so as not to leak, break or allow any discharge.
- c. The reserve would be lined with 12 mil (minimum) thickness polyethylene nylon reinforced liner material. The liner(s) would overlay straw, dirt and/or bentonite if rock is encountered during excavation. The liner would overlap the pit walls and be covered with dirt and/or rocks to hold them in place. No trash, scrap pipe, or other materials that could puncture the liner would be discarded in the pit. A minimum of two feet of free board would be maintained between the maximum fluid level and the top of the reserve pit at all times.
- d. To deter livestock from entering the pit, the three sides exterior to the location would be fenced before drilling starts. Following the conclusion of drilling and completion activities, the fourth side would also be fenced.
- e. Drill cuttings would be contained in the pit and buried on-site for a period not to exceed six months, weather permitting
- f. Produced fluids from the well other than water would be decanted into steel test tank(s) until such time as construction of production facilities is completed. Any oil that may be accumulated would be transferred to a permanent production tank. Produced water may be used in further drilling and completion activities, evaporated in the pit, or would be hauled to one of the following state-approved disposal facilities:

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

Disposal Facilities

- 1. RNI Industries, Inc. Pleasant Valley Disposal Pits, Sec. 25, 26, 35 & 36, T4S-R3W
- 2. Pro Water LLC Blue Bench 13-1 Disposal Well (43-013-30971) NENE, Sec. 13, T3S-R5W
- 3. RN Industries, Inc. Bluebell Disposal Ponds, Sec. 2, 4 & 9, T2S-R2W
- 4. Water Disposal, Inc. Harmston 1-32-A1 Disposal Well (43-013-30224), UTR #00707, Sec. 32, T1S-R1W
- 5. Unified Water Pits Sec. 31, T2S-R4W
- 6. Iowa Tank Line Pits 8500 BLM Fence Road, Pleasant Valley
- 7. Western Water Solutions Sand Pass Ranch, Sections 9 and 10, T4S-R1W, permit #WD-01-2011
- g. Any salts and/or chemicals, which are an integral part of the drilling system, would be disposed of in the same manner as the drilling fluid.
- h. Any spills of oil, condensate, produced or frac water, drilling fluids, or other potentially deleterious substances would be recovered and either returned to its origin or disposed of at an approved disposal site, most likely in Duchesne, Utah.
- i. Chemicals on the EPA's Consolidated List of Chemicals subject to reporting under Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) may be used or stored in quantities over reportable quantities. In the course of drilling, BBC could potentially store and use diesel fuel, sand (silica), hydrochloric acid, and CO₂ gas, all described as hazardous substances in 40 CFR Part 302, Section 302.4, in quantities exceeding 10,000 pounds. In addition, natural gas condensate and crude oil and methanol may be stored or used in reportable quantities. Small quantities of retail products (paint/spray paints, solvents {e.g., WD-40}, and lubrication oil) containing non-reportable volumes of hazardous substances may be stored and used on site at any time. No extremely hazardous substances, as defined in 40 CFR 355, would be used, produced, stored, transported or disposed of in association with the drilling, testing or completion of the wells.
- j. Portable toilets and trash containers would be located onsite during drilling and completion operations. A commercial supplier would install and maintain portable toilets and equipment and would be responsible for removing sanitary waste. Sanitary waste facilities (i.e. toilet holding tanks) would be regularly pumped and their contents disposed of at approved sewage disposal facilities in Duchesne, and/or Uintah Counties, in accordance with applicable rules and regulations regarding sewage treatment and disposal. Accumulated trash and nonflammable waste materials would be hauled to an approved landfill once a week or as often as necessary. All debris and waste materials not contained in the trash containers would be cleaned up, removed from the construction ROW, well pad, or worker housing location, and disposed of at an approved landfill. Trash would be cleaned up everyday.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

- k. Sanitary waste equipment and trash bins would be removed from the Project Area upon completion of access road or pipeline construction; following drilling and completion operations at an individual well pad; when worker housing is no longer needed; or as required.
- 1. A flare pit may be constructed a minimum of 110' from the wellhead(s) and may be used during completion work. In the event a flare pit proves to be unworkable, a temporary flare stack or open top tank would be installed. BBC would flow back as much fluid and gas as possible into pressurized vessels, separating the fluids from the gas. In some instances, due to the completion fluids utilized within the Project Area, it is not feasible to direct the flow stream from the wellbore through pressurized vessels. In such instances BBC proposes to direct the flow to the open top tanks until flow through the pressurized vessels is feasible. At which point the fluid would either be returned to the reserve pit or placed into a tank(s). The gas would be directed to the flare pit, flare stack (each with a constant source of ignition), or may be directed into the sales pipeline.
- m. Hydrocarbons would be removed from the reserve pit would as soon as practical. In the event immediate removal is not practical, the reserve pit would be flagged overhead or covered with wire or plastic mesh to protect migrating birds.

8. <u>Ancillary Facilities:</u>

- a. Garbage containers and portable toilets would be located on the well pad.
- b. On well pads where active drilling and completion is occurring, temporary housing would be provided on location for the well pad supervisor, geologist, tool pusher, and others that are required to be on location at all times. The well pad could include up to five single wide mobile homes or fifth wheel campers/trailers.
- c. A surface powerline corridor 7,014 feet in length is proposed for installation by third-party installer within a 150 foot wide powerline corridor adjacent to the proposed access road. See 12.d below for disturbance estimates. The powerline crosses entirely Ute Tribe surface.

9. Well Site Layout:

- a. The well would be properly identified in accordance with 43 CFR 3162.6.
- b. The pad layout, cross section diagrams and rig layout are enclosed (see Figures 1 and 2).
- c. The pad and road designs are consistent with industry specifications.
- d. The pad has been staked at its maximum size of 400 feet x 300 feet with an inboard reserve pit size of 205 feet x 100 feet x 8 feet deep. See section 12.d below for disturbance estimates.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

- e. Within the approved well pad location, a crawler tractor would strip whatever topsoil is present and stockpile it along the edge of the well pad for use during reclamation. Vegetation would be distributed along the sides of the well pad.
- f. Fill from pit excavation would be stockpiled along the edge of the pit and the adjacent edge of the well pad.
- g. Use of erosion control measures, including proper grading to minimize slopes, diversion terraces and ditches, mulching, terracing, riprap, fiber matting, temporary sediment traps, and broad-based drainage dips or low water crossings would be employed by BBC as necessary and appropriate to minimize erosion and surface runoff during well pad construction and operation. Cut and fill slopes would be constructed such that stability would be maintained for the life of the activity.
- h. All cut and fill slopes would be such that stability can be maintained for the life of the activity.
- i. Diversion ditches would be constructed, if necessary, around the well site to prevent surface waters from entering the well site area.
- j. Water application may be implemented if necessary to minimize the amount of fugitive dust.
- k. All surface disturbing activities would be supervised by a qualified, responsible company representative who is aware of the terms and conditions of the APD and specifications in the approved plans.

10. Plan for Restoration of the Surface:

- a. A site specific reclamation plan would be submitted, if requested, within 90 days of location construction to the surface managing agency.
- b. Site reclamation would be accomplished for portions of the well pad not required for the continued operation of the well on this pad within six months of completion, weather permitting.
- c. The operator would control noxious weeds along access road use authorizations and well site by spraying or mechanical removal, according to the Utah Noxious Weed Act and as set forth in the approved surface damage agreements.
- d. Rat and mouse holes would be filled and compacted from bottom to top immediately upon release of the drilling rig from location. Upon well completion, any hydrocarbons in the pit shall be removed in accordance with 43 CFR 3162.7-1. The reserve pit would be allowed to dry prior to the commencement of backfilling work. No attempts would be made to backfill the

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

reserve pit until it is free of standing water. Once dry, the liner would be torn and perforated before backfilling.

- e. The reserve pit and that portion of the location not needed for production facilities/operations would be recontoured to the approximate natural contours. Areas not used for production purposes would be backfilled and blended into the surrounding terrain, reseeded and erosion control measures installed. Mulching, erosion control measures and fertilization may be required to achieve acceptable stabilization. Back slopes and fore slopes would be reduced as practical and scarified with the contour. The reserved topsoil would be evenly distributed over the slopes and scarified along the contour. Slopes would be seeded with the Ute Tribe specified seed mix.
- f. Topsoil salvaged from the drill site and stored for more than one year would be placed at the location indicated on the well site layout drawing and graded to a depth optimum to maintain topsoil viability, seeded with the Ute Tribe prescribed seed mixture and covered with mulch for protection from wind and water erosion and to discourage the invasion of weeds.

11. Surface and Mineral Ownership:

- a. Surface ownership Ute Indian Tribe 988 South 7500 East; Ft. Duchesne, Utah 84026; 435-725-4982.
- b. Mineral ownership Ute Indian Tribe 988 South 7500 East; Ft. Duchesne, Utah 84026: 435-725-4982.

12. Other Information:

- a. Montgomery Archeological Consultants has conducted a Class III archeological survey. A copy of the report has been submitted under separate cover to the appropriate agencies by Montgomery as report 11-180 dated June 22, 2011.
- b. BBC would require that their personnel, contractors, and subcontractors to comply with Federal regulations intended to protect archeological and cultural resources.
- c. Project personnel and contractors would be educated on and subject to the following requirements:
 - No dogs or firearms within the Project Area.
 - No littering within the Project Area.
 - Smoking within the Project Area would only be allowed in off-operator active locations or in specifically designated smoking areas. All cigarette butts would be placed in appropriate containers and not thrown on the ground or out windows of vehicles; personnel and contractors would abide by all fire restriction orders.
 - Campfires or uncontained fires of any kind would be prohibited.

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

• Portable generators used in the Project Area would have spark arrestors.

d. Disturbance estimates:

Approximate Acreage Disturbances

Well Pad		3.616	acres
Access	7,014 feet	4.810	acres
Pipeline	7,096 feet	4.849	acres
Powerline	7,014 feet	24.050	acres

Total 37.325 acres

Bill Barrett Corporation Surface Use Plan 5-13D-45 BTR Pad Duchesne County, UT

OPERATOR CERTIFICATION

Certification:

I hereby certify that I, or someone under my direction supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein would be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application and that bond coverage is provided under Bill Barrett Corporations federal nationwide bond. These statements are subject to the provisions of 18 U.S.C. 1001 for the filings of false statements.

Executed this

23rd day of Mau

2012

Name:

Venessa Langmacher

Position Title:

Senior Permit Analyst

Address:

1099 18th Street, Suite 2300, Denver, CO 80202

Telephone:

303-312-8172

E-mail:

vlangmacher@billbarrettcorp.com

Field Representative

Kary Eldredge / Bill Barrett Corporation

Address:

1820 W. Highway 40, Roosevelt, UT 84066 435-725-3515 (office); 435-724-6789 (mobile)


Telephone: E-mail:

keldredge@billbarrettcorp.com

Venessa Langmacher, Senior Permit Analyst


BILL BARRETT CORPORATION

TYPICAL 5,000 p.s.i. BLOWOUT PREVENTER



BILL BARRETT CORPORATION

TYPICAL 5,000 p.s.i. CHOKE MANIFOLD





May 23, 2012

Ms. Diana Mason – Petroleum Technician State of Utah Division of Oil, Gas and Mining 1594 West North Temple, Suite 1210 P. O. Box 145801 Salt Lake City, Utah 84114-5801

Re: Directional Drilling R649-3-11

Blacktail Ridge Area #5-13D-45 BTR Well

Surface: 2,079' FNL & 868' FWL, SWNW, 13-T4S-R5W, USM Bottom Hole: 1,980' FNL & 810' FWL, SWNW, 13-T4S-R5W, USM

Duchesne County, Utah

Dear Ms. Mason,

Pursuant to the filing of Bill Barrett Corporation's ("BBC") Application for Permit to Drill the above referenced well, we hereby submit this letter in accordance with Oil & Gas Conservation Rules R649-2, R649-3, R649-10 and R649-11, pertaining to the Location and Siting of Wells.

- The proposed location is within our Blacktail Ridge Area.
- BBC is permitting this well as a directional well in order to minimize surface disturbance. By locating the well at the surface location and directionally drilling from this location, BBC will be able to utilize the existing road and pipelines in the area.
- The well will be drilled under an Exploration and Development Agreement between the Ute Indian Tribe and Ute Distribution Corporation. Ute Energy, LLC owns a right to participate in this well.
- BBC certifies that it is the working interest owner of all lands within 460 feet of the proposed well location, and together with Ute Energy, LLC, we own 100% of the working interest in these lands.


Based on the information provided, BBC requests that the permit be granted pursuant to R649-3-11. Should you have any questions or need further information, please contact me at 303-312-8544.


Sincerely, angmaches for


David Watts


Landman


1099 18TH STREET
SUITE 2300
DENVER, CO 80202
P 303.293.9100
F 303.291.0420











API Well Number: 43013514460000

WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 5/23/2012 **API NO. ASSIGNED:** 43013514460000

WELL NAME: 5-13D-45 BTR

OPERATOR: BILL BARRETT CORP (N2165) **PHONE NUMBER:** 303 312-8172

CONTACT: Venessa Langmacher

PROPOSED LOCATION: SWNW 13 040S 050W Permit Tech Review:

SURFACE: 2079 FNL 0868 FWL Engineering Review:

BOTTOM: 1980 FNL 0810 FWL Geology Review:

COUNTY: DUCHESNE

LATITUDE: 40.13467 LONGITUDE: -110.40500 UTM SURF EASTINGS: 550689.00 NORTHINGS: 4442874.00

FIELD NAME: DUCHESNE LEASE TYPE: 2 - Indian

LEASE NUMBER: 20G0005608 **PROPOSED PRODUCING FORMATION(S):** GREEN RIVER-WASATCH

SURFACE OWNER: 2 - Indian COALBED METHANE: NO

RECEIVED AND/OR REVIEWED: LOCATION AND SITING:

▶ PLAT R649-2-3.

Bond: INDIAN - LPM8874725 Unit:

Potash R649-3-2. General

Oil Shale 190-5

Oil Shale 190-3 R649-3-3. Exception

Oil Shale 190-13

Water Permit: 43-180 Board Cause No: Cause 139-85

RDCC Review: Effective Date: 3/11/2010

Fee Surface Agreement Siting: 4 Prod LGRRV-WSTC Per Sectional Drilling Units

Intent to Commingle R649-3-11. Directional Drill


Commingling Approved

Comments: Presite Completed

Stipulations: 4 - Federal Approval - dmason

15 - Directional - dmason

RECEIVED: June 07, 2012



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

Permit To Drill

Well Name: 5-13D-45 BTR **API Well Number:** 43013514460000

Lease Number: 20G0005608 Surface Owner: INDIAN

Approval Date: 6/7/2012

Issued to:

BILL BARRETT CORP, 1099 18th Street Ste 2300, Denver, CO 80202

Authority:

Pursuant to Utah Code Ann. 40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 139-85. The expected producing formation or pool is the GREEN RIVER-WASATCH Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

General:

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

Notification Requirements:

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

• Within 24 hours following the spudding of the well - contact Carol Daniels at 801-538-5284

(please leave a voicemail message if not available)

OR

submit an electronic sundry notice (pre-registration required) via the Utah Oil &

Reporting Requirements:

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) due within 5 days of spudding the well
- Monthly Status Report (Form 9) due by 5th day of the following calendar month
 - Requests to Change Plans (Form 9) due prior to implementation
 - Written Notice of Emergency Changes (Form 9) due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) due prior to implementation
 - Report of Water Encountered (Form 7) due within 30 days after completion
- Well Completion Report (Form 8) due within 30 days after completion or plugging

Approved By:

For John Rogers Associate Director, Oil & Gas Form 3160-3 (August 2007)

RECEIVED

UNITED STATES

FORM APPROVED OMB No. 1004-0136 Expires July 31, 2010

Lease Serial No. 20G0005608

DEPARTMENT OF THE INTERIOR MAY 2 9 2012 BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT	6. If Indian, Allottee or Tribe Name			
1a. Type of Work: ☑ DRILL ☐ REENTER		7. If Unit or CA Agreement, Name and No.		
1b. Type of Well: ☑ Oil Well ☐ Gas Well ☐ Ot 2. Name of Operator Contact: BILL BARRETT CORPORATION E-Mail: vlangma	her Single Zone Multiple Zone VENESSA LANGMACHER acher@billbarrettcorp.com	8. Lease Name and Well No. 5-13D-45 BTR 9. API Well No.		
3a. Address 1099 18TH STREET SUITE 2300 DENVER, CO 80202	3b. Phone No. (include area code) Ph: 303-312-8172 Fx: 303-291-0420	10. Field and Pool, or Exploratory UNDESIGNATED		
4. Location of Well (Report location clearly and in accord		11. Sec., T., R., M., or Blk. and Survey or Area		
	. 40.134747 N Lat, 110.405031 W Lon	Sec 13 T4S R5W Mer UBM		
At proposed prod. zone SWNW 1980FNL 810FWL				
14. Distance in miles and direction from nearest town or post 5.8 MILES SOUTH OF DUCHESNE, UT	office*	12. County or Parish 13. State DUCHESNE UT		
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any)	16. No. of Acres in Lease	17. Spacing Unit dedicated to this well		
810' (BTM. HOLE)	66101.00	640.00		
 Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 	19. Proposed Depth	20. BLM/BIA Bond No. on file		
NONE	9220 MD 9218 TVD	LPM8874725		
21. Elevations (Show whether DF, KB, RT, GL, etc. 6223 GL	22. Approximate date work will start 11/01/2013	23. Estimated duration 60 DAYS (D&C)		
	24. Attachments	RECEIVED		
The following, completed in accordance with the requirements of Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest Syste SUPO shall be filed with the appropriate Forest Service Off	4. Bond to cover the operation Item 20 above). 5. Operator certification	his form: J. J. 3 1 2013 Is unless covered by an existing bond on file (see DIV. OF OIL, GAS & MINING Ormation and/or plans as may be required by the		
25. Signature (Electronic Submission)	Name (Printed/Typed) VENESSA LANGMACHER Ph: 303-312	-8172 Date 05/23/2012		
Title SENIOR PERMIT ANALYST				
Approved by (Signaturant Field Manager Lands & Mineral Resources Title	Name (Printed/Typed) Jerry Kenczk	a Date JAN 2 2 2013		
	VERNAL FIELD OFFICE			
pplication approval does not warrant or certify the applicant holperations thereon.				
onditions of approval, if any, are attached.	CONDITIO	NS OF APPROVAL ATTACHED		
itle 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, n tates any false, fictitious or fraudulent statements or representati		make to any department or agency of the United		
dditional Operator Remarks (see next page)				

Electronic Submission #138835 verified by the BLM Well Information System For BILL BARRETT CORPORATION, sent to the Vernal Committed to AFMSS for processing by LESLIE ROBINSON on 05/29/2012 ()

NOTICE OF APPROVAL

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

12PPH1950AZ



UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT VERNAL FIELD OFFICE**

VERNAL, UT 84078

(435) 781-4400



CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company: Well No:

BILL BARRETT CORPORATION

5-13D-45 BTR

API No: 43-013-51446 Location: Lease No: SWNW, Sec. 13, T4S, R5W

2OG0005608

Agreement:

N/A

OFFICE NUMBER:

(435) 781-4400

OFFICE FAX NUMBER: (435) 781-3420

A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR FIELD REPRESENTATIVE TO INSURE COMPLIANCE

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.

NOTIFICATION REQUIREMENTS

Construction Activity (Notify Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist)	-	The Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist shall be notified at least 48 hours in advance of any construction activity. The Ute Tribal office is open Monday through Thursday.
Construction Completion (Notify Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist)	-	Upon completion of the pertinent APD/ROW construction, notify the Ute Tribe Energy & Minerals Dept. for a Tribal Technician to verify the Affidavit of Completion. Notify the BLM Environmental Scientist prior to moving on the drilling rig.
Spud Notice (Notify BLM Petroleum Engineer)	-	Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify BLM Supv. Petroleum Tech.)	-	Twenty-Four (24) hours prior to running casing and cementing all casing strings to: blm_ut_vn_opreport@blm.gov.
BOP & Related Equipment Tests (Notify BLM Supv. Petroleum Tech.)	-	Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify BLM Petroleum Engineer)		Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

Additional Stipulations:

- All Production Equipment will be painted Beetle Green to help blend into the surrounding vegetation and meet VRM type objectives.
- The production equipment will be placed towards the front of the pad to maximize interim reclamation efforts on all well pads where applicable.
- See Exhibit One of the approved EA U&O-FY13-Q1-025 for any additional mitigation measures that must be followed for this proposed action.
- Also any site specific mitigation measures attached to the Applications for Permit to Drill, specifically those found at the beginning of the surface use plan of operations will be required and followed as indicated.

General Conditions of Approval:

- A <u>30'</u> foot corridor right-of-way shall be approved. Upon completion of each pipeline in corridor, they shall be identified and filed with the Ute Tribe.
- The Ute Tribe Energy & Minerals Department is to be notified, in writing 48 hours prior to construction of pipelines.
- Construction Notice shall be given to the department on the Ute Tribe workdays, which are Monday through Thursday. The Company understands that they may be responsible for costs incurred by the Ute Tribe after hours.
- The Company shall inform contractors to maintain construction of pipelines within the approved ROW's.
- The Company shall assure the Ute Tribe that "ALL CONTRACTORS, INCLUDING SUB-CONTRACTORS, LEASING CONTRACTORS, AND ETC." have acquired a current and valid Ute Tribal Business License and have "Access Permits" prior to construction, and will have these permits in all vehicles at all times.
- You are hereby notified that working under the "umbrella" of a company does not allow you to be in the field, and can be subject to those fines of the Ute Tribe Severance Tax Ordinance.
- Any deviation of submitted APD's and ROW applications the Companies will notify the Ute Tribe and BIA in writing and will receive written authorization of any such change with appropriate authorization.
- Bill Barrett Corporation will implement a "Safety and Emergency Plan." The Company's safety director will ensure its compliance.
- All Company employees and/or authorized personnel (sub-contractors) in the field will have approved applicable APD's, COA's, and/or ROW permits/authorizations on their person(s) during all phases of construction.
- All vehicular traffic, personnel movement, construction/restoration operations should be confined to the area examined and approved, and to the existing roadways and/or evaluated access routes.
- The personnel from the Ute Tribe Energy & Minerals Department should be notified should cultural remains from subsurface deposits be exposed or identified during construction. All construction will cease.
- Upon completion of Application for Corridor Right-Way, the company will notify the Ute Tribe Energy & Minerals Department, so that a Tribal Technician can verify Affidavit of Completion.

Page 3 of 6 Well: 5-13 D-45 BTR 1/16/2013

DOWNHOLE PROGRAM CONDITIONS OF APPROVAL (COAs)

SITE SPECIFIC DOWNHOLE COAs:

- A formation integrity test shall be performed at the surface casing shoe.
- Gamma Ray Log shall be run from Total Depth to Surface.
- To effectively protect useable water, cement for the long string is required to be brought 200 feet above the surface casing shoe

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- All requirements listed in Onshore Order #2 III. E. Special Drilling Operations are applicable for air drilling of surface hole.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the
 daily drilling report. Components shall be operated and tested as required by Onshore Oil &
 Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be
 performed by a test pump with a chart recorder and <u>NOT</u> by the rig pumps. Test shall be
 reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- Cement baskets shall not be run on surface casing.

Page 4 of 6 Well: 5-13D-45 BTR 1/16/2013

- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water
 is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM
 Vernal Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.
- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM,
 Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the <u>top of cement</u> and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- Please submit an electronic copy of all other logs run on this well by CD (compact disc). This submission will supersede the requirement for submittal of paper logs to the BLM.
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

Page 5 of 6 Well: **S~13**D-45 BTR 1/16/2013

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- Should the well be successfully completed for production, the BLM Vernal Field office must be
 notified when it is placed in a producing status. Such notification will be by written
 communication and must be received in this office by not later than the fifth business day
 following the date on which the well is placed on production. The notification shall provide, as a
 minimum, the following informational items:
 - o Operator name, address, and telephone number.
 - Well name and number.
 - Well location (¼¼, Sec., Twn, Rng, and P.M.).
 - Date well was placed in a producing status (date of first production for which royalty will be paid).
 - o The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - o Unit agreement and/or participating area name and number, if applicable.
 - o Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if

Page 6 of 6 Well: **5 -13**D-45 BTR 1/16/2013

performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field
 Office Petroleum Engineers will be provided with a date and time for the initial meter calibration
 and all future meter proving schedules. A copy of the meter calibration reports shall be
 submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API
 standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All
 measurement points shall be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted
 to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs
 first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be
 adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively
 sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover
 equipment shall be removed from a well to be placed in a suspended status without prior
 approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30
 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given
 before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

Sundry Number: 37900 API Well Number: 43013514460000

				FORM
	5.LEASE DESIGNATION AND SERIAL NUMBER 20G0005608			
SUNDR	RY NOTICES AND REPORTS	ON V	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: Uintah
	oposals to drill new wells, significantly reenter plugged wells, or to drill horizon for such proposals.			7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well				8. WELL NAME and NUMBER: 5-13D-45 BTR
2. NAME OF OPERATOR: BILL BARRETT CORP				9. API NUMBER: 43013514460000
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202		NE NUMBER: 12-8134 Ext	9. FIELD and POOL or WILDCAT: DUCHESNE
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2079 FNL 0868 FWL				COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 13 Township: 04.0S Range: 05.0W Me	eridian:	U	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICA	ATE NA	ATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
	ACIDIZE		LTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	С	HANGE TUBING	CHANGE WELL NAME
6/1/2014	CHANGE WELL STATUS	□ co	OMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN		RACTURE TREAT	NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE		LUG AND ABANDON	PLUG BACK
	PRODUCTION START OR RESUME		ECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	_			
Date of Spau.	REPERFORATE CURRENT FORMATION		DETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON
_	L TUBING REPAIR		ENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	∟ sı	TA STATUS EXTENSION	✓ APD EXTENSION
	WILDCAT WELL DETERMINATION	o	THER	OTHER:
I .	COMPLETED OPERATIONS. Clearly show	-		lepths, volumes, etc.
BBC hereby red	quests a one year extension	for t	he subject APD.	Approved by the
				Utah Division of Oil, Gas and Mining
				_
				Date: May 20, 2013
				By: Bacquill
NAME (PLEASE PRINT) Venessa Langmacher	PHONE NUMB 303 312-8172	IBER	TITLE Senior Permit Analyst	
SIGNATURE N/A			DATE 5/15/2013	

Sundry Number: 37900 API Well Number: 43013514460000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013514460000

API: 43013514460000 Well Name: 5-13D-45 BTR

Location: 2079 FNL 0868 FWL QTR SWNW SEC 13 TWNP 040S RNG 050W MER U

Company Permit Issued to: BILL BARRETT CORP

Date Original Permit Issued: 6/7/2012

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

·· · ·
• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Q Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
 Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
 Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? 🔵 Yes 🌘 No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
nature: Venessa Langmacher Date: 5/15/2013

Signature: Venessa Langmacher

Title: Senior Permit Analyst Representing: BILL BARRETT CORP

Sundry Number: 50927 API Well Number: 43013514460000

	STATE OF UTAH DEPARTMENT OF NATURAL RESOUF				FORM 9		
ı	5.LEASE I 20G000	DESIGNATION AND SERIAL NUMBER: 05608					
SUNDRY NOTICES AND REPORTS ON WELLS					AN, ALLOTTEE OR TRIBE NAME:		
Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.					7.UNIT or CA AGREEMENT NAME:		
1. TYPE OF WELL Oil Well				8. WELL N 5-13D-4	IAME and NUMBER: 15 BTR		
2. NAME OF OPERATOR: BILL BARRETT CORP				9. API NUI 430135	MBER: 14460000		
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202		NE NUMBER: 312-8134 Ext	9. FIELD a	and POOL or WILDCAT: NE		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2079 FNL 0868 FWL				COUNTY: DUCHES			
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SWNW Section:	HP, RANGE, MERIDIAN: 13 Township: 04.0S Range: 05.0W M	eridian	ı: U	STATE: UTAH			
11. CHECI	K APPROPRIATE BOXES TO INDICA	ATE N	ATURE OF NOTICE, REPOR	RT, OR OT	HER DATA		
TYPE OF SUBMISSION			TYPE OF ACTION				
	ACIDIZE		ALTER CASING		CASING REPAIR		
Approximate date work will start:	CHANGE TO PREVIOUS PLANS		CHANGE TUBING		CHANGE WELL NAME		
6/7/2014	CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS		CONVERT WELL TYPE		
SUBSEQUENT REPORT	DEEPEN	☐ F	FRACTURE TREAT		NEW CONSTRUCTION		
Date of Work Completion:	OPERATOR CHANGE	Пр	PLUG AND ABANDON		PLUG BACK		
	PRODUCTION START OR RESUME		RECLAMATION OF WELL SITE		RECOMPLETE DIFFERENT FORMATION		
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL		TEMPORARY ABANDON		
	TUBING REPAIR		/ENT OR FLARE		WATER DISPOSAL		
 					APD EXTENSION		
DRILLING REPORT Report Date:	WATER SHUTOFF	□ s	SI TA STATUS EXTENSION	•	APD EXTENSION		
	WILDCAT WELL DETERMINATION		OTHER	OTHER	t:		
	COMPLETED OPERATIONS. Clearly show						
BBC ner	eby request a one extension	n ior	Said APD		Approved by the Utah Division of		
					I, Gas and Mining May 12, 2014		
					May 12, 2014		
				Date:_	Million d		
				Ву:	Didollar		
					Q G		
NAME (PLEASE PRINT)	PHONE NUM	IBER	TITLE				
Christina Hirtler	303 312-8597		Administrative Assistant				
SIGNATURE N/A			DATE 5/8/2014				

Sundry Number: 50927 API Well Number: 43013514460000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013514460000

API: 43013514460000 **Well Name:** 5-13D-45 BTR

Location: 2079 FNL 0868 FWL QTR SWNW SEC 13 TWNP 040S RNG 050W MER U

Company Permit Issued to: BILL BARRETT CORP

Date Original Permit Issued: 6/7/2012

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of thi proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? (Yes (No
• Has the approved source of water for drilling changed? Yes No
• Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
natura. Christina Hirtler Data. 5/9/2014

Signature: Christina Hirtler Date: 5/8/2014

Title: Administrative Assistant Representing: BILL BARRETT CORP

Sundry Number: 62999 API Well Number: 43013514460000

	STATE OF UTAH		FORM 9
	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MIN		5.LEASE DESIGNATION AND SERIAL NUMBER: 20G0005608
SUNDF	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
	oposals to drill new wells, significantly reenter plugged wells, or to drill horizo n for such proposals.		7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: 5-13D-45 BTR
2. NAME OF OPERATOR: BILL BARRETT CORP			9. API NUMBER: 43013514460000
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202	PHONE NUMBER: 303 312-8134 Ext	9. FIELD and POOL or WILDCAT: DUCHESNE
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2079 FNL 0868 FWL			COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSI Qtr/Qtr: SWNW Section:	HIP, RANGE, MERIDIAN: 13 Township: 04.0S Range: 05.0W Me	ridian: U	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
6/7/2015	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	_		
Date of Space.	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	LI TEMPORARY ABANDON
	L TUBING REPAIR	☐ VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
	WILDCAT WELL DETERMINATION	OTHER	OTHER:
	COMPLETED OPERATIONS. Clearly show		
BBC her	eby request a one extension	for said APD	Approved by the
			UMaly D5/i2/01/50f Oil, Gas and Mining
			-
			Date:
			By: Doddy
NAME (PLEASE PRINT)	PHONE NUMB		
Brady Riley	303 312-8115	Permit Analyst	
SIGNATURE N/A		DATE 5/4/2015	

Sundry Number: 62999 API Well Number: 43013514460000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013514460000

API: 43013514460000 **Well Name:** 5-13D-45 BTR

Title: Permit Analyst Representing: BILL BARRETT CORP

Location: 2079 FNL 0868 FWL QTR SWNW SEC 13 TWNP 040S RNG 050W MER U

Company Permit Issued to: BILL BARRETT CORP

Date Original Permit Issued: 6/7/2012

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

to distance of some from rolated to the approacher, which chests so verified.
• If located on private land, has the ownership changed, if so, has the surface agreement been updated? 🔘 Yes 📵 No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
 Has there been any unit or other agreements put in place that could affect the permitting or operation of the proposed well? Yes No
 Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? 🔵 Yes 📵 No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? 🌘 Yes 💭 No
Signature: Brady Riley Date: 5/4/2015

RECEIVED: May. 04, 2015

Sundry Number: 70880 API Well Number: 43013514460000

	STATE OF UTAH		FORM 9
	5.LEASE DESIGNATION AND SERIAL NUMBER:		
	DIVISION OF OIL, GAS, AND MIN	NING	2OG0005608
SUNDR	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
	oposals to drill new wells, significantly reenter plugged wells, or to drill horizon for such proposals.		7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: 5-13D-45 BTR
2. NAME OF OPERATOR: BILL BARRETT CORP			9. API NUMBER: 43013514460000
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202	PHONE NUMBER: 303 312-8134 Ext	9. FIELD and POOL or WILDCAT: DUCHESNE
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2079 FNL 0868 FWL			COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 13 Township: 04.0S Range: 05.0W Mer	ridian: U	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
6/7/2017	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
	_		
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	☐ NEW CONSTRUCTION
	OPERATOR CHANGE	PLUG AND ABANDON	L PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
Report Date:	WILDCAT WELL DETERMINATION	OTHER	OTHER:
42 DESCRIPE PROPOSED OR			Janatha Waliumaa ata
I .	COMPLETED OPERATIONS. Clearly show the completed operations and show the complete co		Approved by the
BBO is ficiosy requi	6/7/2017.		UtphilD05js2016f Oil, Gas and Mining
			-
			Date:
			By: Dady
NAME (PLEASE PRINT)	PHONE NUMB		
Brady Riley	303 312-8115	Permit Analyst	
SIGNATURE N/A		DATE 4/4/2016	

Sundry Number: 70880 API Well Number: 43013514460000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013514460000

API: 43013514460000 Well Name: 5-13D-45 BTR

Location: 2079 FNL 0868 FWL QTR SWNW SEC 13 TWNP 040S RNG 050W MER U

Company Permit Issued to: BILL BARRETT CORP

Date Original Permit Issued: 6/7/2012

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of thi proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? (Yes (No
• Has the approved source of water for drilling changed? Yes No
• Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
nature: Brady Biley Date: 4/4/2016

Signature: Brady Riley **Date:** 4/4/2016

Title: Permit Analyst Representing: BILL BARRETT CORP

Division of Oil, Gas and Mining

Operator Change/Name Change Worksheet-for State use only

Effective Date:

11/1/2016

FORMER OPERATOR:	NEW OPERATOR:
Bill Barrett Corporation	Rig II, LLC
1099 18th Street, Suite 2300	1582 West 2600 South
Denver, CO 80202	Woods Cross, UT 84087
CA Number(s):	Unit(s):

WELL INFORMATION:

Well Name	Sec	TWN	RNG	API	Entity	Mineral	Surface	Type	Status
See Attached List									

OPERATOR CHANGES DOCUMENTATION:

1. Sundry or legal documentation was received from the **FORMER** operator on:

10/21/2016

2. Sundry or legal documentation was received from the **NEW** operator on:

10/21/2016

3. New operator Division of Corporations Business Number:

8256968-0160

REVIEW:

1. Surface Agreement Sundry from NEW operator on Fee Surface wells received on:

N/A

2. Receipt of Acceptance of Drilling Procedures for APD on:

10/21/2016

3. Reports current for Production/Disposition & Sundries:

11/2/2016

4. OPS/SI/TA well(s) reviewed for full cost bonding:

11/3/2016

5. UIC5 on all disposal/injection/storage well(s) approved on:

11/3/2016

6. Surface Facility(s) included in operator change:

None

7. Inspections of PA state/fee well sites complete on (only upon operators request):

11/3/2016

NEW OPERATOR BOND VERIFICATION:

1. Federal well(s) covered by Bond Number:

UTB000712

2. Indian well(s) covered by Bond Number:

LPM 922467

3.State/fee well(s) covered by Bond Number(s):

9219529

DATA ENTRY:

1. Well(s) update in the OGIS on:

11/7/2016

2. Entity Number(s) updated in OGIS on:

11/7/2016

3. Unit(s) operator number update in OGIS on:

N/A

4. Surface Facilities update in OGIS on:

N/A

5. State/Fee well(s) attached to bond(s) in RBDMS on:

11/7/2016

6. Surface Facilities update in RBDMS on:

N/A

COMMENTS:

Well Name	Sec	TWN	RNG	API Number	Entity	Mineral	Surface	Туре	Status
SWD 9-36 BTR	9	030S	060W	4301350646	18077	Indian	Fee	WD	Α
16-6D-46 BTR SWD	6	040S	060W	4301350781	18327	Indian	Fee	WD	Α
6-32-36 BTR SWD	32	030S	060W	4301350921	18329	Indian	Fee	WD	Α
LC TRIBAL 8-26D-47	26	040S	070W	4301334024		Indian	Indian	OW	APD
16-21D-37 BTR	21	030S	070W	4301350758		Indian	Fee	OW	APD
14-11D-37 BTR	11	030S	070W	4301350862		Indian	Fee	OW	APD
7-17D-46 BTR	17	040\$	060W	4301350883		Indian	Indian	OW	APD
14-12D-37 BTR	12	030S	070W	4301350894		Indian	Fee	OW	APD
1-18D-36 BTR	18	030S	060W	4301350922		Indian	Fee	OW	APD
13-2D-45 BTR	2	040S	050W	4301350931		Indian	Indian	OW	APD
5H-16-46 BTR	16	040S	060W	4301350992		Indian	Indian	OW	APD
9H-17-45 BTR	17	040S	050W	4301351098		Indian	Indian	OW	APD
13H-8-46 BTR UB	8	040S	060W	4301351124		Indian	Indian	OW	APD
BH-9-46 BTR	9	040S	060W	4301351140		Indian	Indian	ow	APD
_C TRIBAL 7-31D-37	31	030S	070W	4301351147		Indian	Fee	ow	APD
14-16D-45 BTR	16	040S	050W	4301351178		Indian	Indian	ow	APD
16-19D-37 BTR	19	030S	070W	4301351179		Indian	Fee	OW	APD
6-2D-45 BTR	2	040S	050W	4301351234		Indian	Indian	ow	APD
2-2D-45 BTR	2	040S	050W	4301351235		Indian	Indian	ow	APD
10-26-35 BTR	26	030S	050W	4301351248		Indian	Fee	OW	APD
C TRIBAL 1H-33-46	33	040S	060W	4301351257		Indian	Fee	ow	APD
_C TRIBAL 9-25D-46	25	040S	060W	4301351276		Indian	Indian	ow	APD
C TRIBAL 8H-30-45	30	040S	050W	4301351277	(8.7)	Indian	Indian	OW	APD
_C TRIBAL 16H-30-45	30	040S	050W	4301351279		Indian	Indian	ow	APD
_C TRIBAL 13-30D-45	30	040S	050W	4301351282		Indian	Indian	ow	APD
_C TRIBAL 16H-36-46	36	040S	060W	4301351291		Indian	Indian	OW	APD
C TRIBAL 13H-30-46	30	040S	060W	4301351321		Indian	Indian	OW	APD
C TRIBAL 13H-31-46	31	040S	060W	4301351326		Indian	Indian	OW	APD
_C TRIBAL 16-31D-46	31	040S	060W	4301351328		Indian	Indian	OW	APD
C TRIBAL 5H-26-47	26	040S	070W	4301351337		Indian	Indian	OW	APD
_C TRIBAL 5H-19-45	20	040S	050W	4301351349		Indian	Indian	OW	APD
C TRIBAL 16-36D-47	36	040S	070W	4301351363		Indian	Indian	OW	APD
15-4D-47 BTR	4	040S	070W	4301351377		Indian	Fee	OW	APD
16-23D-46 LC TRIBAL	23	040S	060W	4301351396		Indian	Fee	ow	APD
15-2D-36 BTR	2	030S	060W	4301351419		Indian	Fee	OW	APD
16-23D-37 BTR	23	030S	070W	4301351420	1	Indian	Fee	ow	APD
11-9D-47 BTR	9	040S	070W	4301351422		Indian	Fee	OW	APD
15-13D-47 BTR	13	040S	070W	4301351424		Indian	Indian	OW	APD
_C TRIBAL 15-19D-46	19	040S	060W	4301351426		Indian	Indian	OW	APD
16-13D-45 BTR	13	040S	050W	4301351428		Indian	Indian	OW	APD

14-12D-45 BTR	12	040S	050W	4301351444	Indian	Indian	OW	APD
16-14D-45 BTR	14	040S	050W	4301351445	Indian	Indian	OW	APD
5-13D-45 BTR	13	040S	050W	4301351446	Indian	Indian	OW	APD
LC TRIBAL 16-26D-46	26	040S	060W	4301351450	Indian	State	OW	APD
LC TRIBAL 10-20D-40	34	0408	060W	4301351451				
16-12D-45 BTR	12	040S	050W	4301351451	Indian Indian	State Indian	OW	APD
8-12D-45 BTR	12	040S	050W	4301351452			OW	APD
LC TRIBAL 1-35D-46	35	040S	060W		Indian	Indian	OW	APD
16-25D-37 BTR		0405	070W	4301351454	Indian	Fee	OW	APD
LC TRIBAL 13H-29-46	25			4301351455	Indian	Fee	OW	APD
	28	0408	060W	4301351462	Indian	Fee	OW	APD
LC TRIBAL 14-30D-37	30	0308	070W	4301351494	Indian	Fee	OW	APD
7-13D-45 BTR	13	0408	050W	4301351497	Indian	Indian	OW	APD
LC TRIBAL 4H-35-46	35	0408	060W	4301351515	Indian	Fee	OW	APD
LC TRIBAL 13H-19-46	19	040\$	060W	4301351543	Indian	Indian	OW	APD
16-26D-37 BTR	26	030S	070W	4301351598	Indian	Fee	OW	APD
LC TRIBAL 16-31D-37	31	030\$	070W	4301351610	Indian	Fee	OW	APD
5-4-35 BTR	4	030S	050W	4301351613	Indian	Fee	OW	APD
LC TRIBAL 16-31D-47	31	040S	070W	4301351616	Indian	Indian	OW	APD
LC TRIBAL 13H-31-47	31	040S	070W	4301351617	Indian	Indian	OW	APD
LC TRIBAL 13-32D-47	32	040S	070W	4301351619	Indian	Indian	OW	APD
LC TRIBAL 16H-32-47	32	040S	070W	4301351620	Indian	Indian	OW	APD
LC TRIBAL 1-32D-47	32	040S	070W	4301351624	Indian	Indian	OW	APD
LC TRIBAL 4H-32-47	32	040S	070W	4301351625	Indian	Indian	OW	APD
LC TRIBAL 13-28D-47	28	040S	070W	4301351627	Indian	Indian	OW	APD
LC TRIBAL 13H-29-47	28	040S	070W	4301351628	Indian	Indian	OW	APD
LC TRIBAL 16H-28-47	28	040S	070W	4301351629	Indian	Indian	OW	APD
LC TRIBAL 1-28D-47	28	040S	070W	4301351639	Indian	Indian	OW	APD
LC TRIBAL 1H-27-47	28	040S	070W	4301351640	Indian	Indian	OW	APD
LC TRIBAL 4H-28-47	28	040S	070W	4301351641	Indian	Indian	OW	APD
LC TRIBAL 7-25D-58	25	050S	W080	4301351643	Indian	Indian	OW	APD
LC TRIBAL 6-25D-58	25	050S	080W	4301351644	Indian	Indian	OW	APD
LC TRIBAL 13H-24-58	24	050S	W080	4301351645	Indian	Indian	OW	APD
LC TRIBAL 16-24D-58	24	050S	080W	4301351646	Indian	Indian	OW	APD
LC Tribal 8-23D-46	23	040S	060W	4301351654	Indian	Fee	OW	APD
LC Tribal 16-35D-45	35	040S	050W	4301351656	Indian	Fee	OW	APD
LC Tribal 13H-35-45	35	040S	050W	4301351657	Indian	Fee	ow	APD
LC Tribal 16-36D-45	36	040S	050W	4301351658	Indian	Fee	ow	APD
LC Tribal 13H-36-45	36	040S	050W	4301351659	Indian	Fee	OW	APD
LC Tribal 5-36D-45	36	0408	050W	4301351661	Indian	Fee	OW	APD
LC Tribal 8-26D-46	26	040\$	060W	4301351663	Indian	Fee	OW	APD
3-29D-36 BTR	29	0308	060W	4301351665	Indian	Fee	OW	APD

LC Tribal 5-35D-45	35	040S	050W	4301351666	Indian	Fee	OW	APD
_C Tribal 5-24D-46	24	0408	060W	4301351668	Indian	Indian	OW	APD
C TRIBAL 6-12D-58	12	0508	080W	4301351696	Indian	Indian	OW	APD
_C TRIBAL 8-12D-58	12	050S	080W	4301351697	Indian	Indian	OW	APD
.C TRIBAL 16H-22-47	21	040S	070W	4301351700	Indian	Indian	OW	APD
5-25D-37 BTR	25	0308	070W	4301351803	Indian	Fee	OW	APD
8-3D-36 BTR	3	0308	060W	4301351804	Indian	Fee	OW	APD
14-26D-37 BTR	26	0308	070W	4301351805	Indian	Fee	OW	APD
9-4-35 BTR	4	0308	050W	4301351806	Indian	Fee	ow	APD
11-4D-35 BTR	4	030S	050W	4301351807	Indian	Fee	OW	APD
6-27D-37 BTR	27	0308	070W	4301351808	Indian	Fee	OW	APD
14-27D-37 BTR	27	0308	070W	4301351809	Indian	Fee	OW	APD
14-16D-46 BTR	16	040S	060W	4301351812	Indian	Indian	OW	APD
_C Tribal 16-35D-48	35	0408	080W	4301351847	Indian	Indian	OW	APD
_C Tribal 13H-35-48	35	040S	080W	4301351848	Indian	Indian	OW	APD
_C Tribal 13-2D-58	11	050S	080W	4301351850	Indian	Indian	OW	APD
5-13D-36 BTR	13	030S	060W	4301351862	Indian	Fee	OW	APD
5-8D-36 BTR	8	0308	060W	4301351871	Indian	Fee	OW	APD
16-1D-36 BTR	1	0308	060W	4301351872	Indian	Fee	ow	APD
3-18D-46 BTR	18	040S	060W	4301351897	Indian	Fee	OW	APD
_C Tribal 5-36D-46	36	0408	060W	4301351905	Indian	Indian	OW	APD
LC Tribal 5-26D-45	26	040S	050W	4301351907	Indian	Indian	OW	APD
14-13D-45 BTR	13	040S	050W	4301351974	Indian	Indian	OW	APD
14-34D-46 DLB	34	040S	060W	4301351975	Indian	Fee	OW	APD
C Tribal 5-21D-45	21	0408	050W	4301352001	Indian	Indian	OW	APD
_C Tribal 8-22D-45	22	0408	050W	4301352002	Indian	Indian	OW	APD
_C Tribal 8-25D-45	25	0408	050W	4301352007	Indian	Indian	OW	APD
_C Tribal 16-25D-45	25	040S	050W	4301352008	Indian	Indian	OW	APD
LC Tribal 16-22D-45	22	040S	050W	4301352009	Indian	Indian	OW	APD
LC Tribal 16-26D-45	26	0408	050W	4301352010	Indian	Indian	OW	APD
_C Tribal 14-31D-37	31	0308	070W	4301352016	Indian	Fee	OW	APD
5-12D-45 BTR	12	040S	050W	4301352030	Indian	Indian	OW	APD
_C Tribal 9-20D-45	20	040S	050W	4301352031	Indian	Indian	OW	APD
LC Tribal 13-35D-47	35	0408	070W	4301352055	Indian	Indian	OW	APD
_C Tribal 1-23D-47	23	040S	070W	4301352057	Indian	Indian	ow =	APD
9-17D-46 BTR	17	040S	060W	4301352059	Indian	Indian	OW	APD
11-18D-46 BTR	18	040S	060W	4301352060	Indian	Indian	OW	APD
9-10D-47 BTR	10	040S	070W	4301352092	Indian	Fee	OW	APD
LC Tribal 1-17D-47	17	0408	070W	4301352096	Indian	Fee	OW	APD
7-35D-37 BTR	35	0308	070W	4301352115	Indian	Fee	OW	APD
14-25D-37 BTR	25	0308	070W	4301352116	Indian	Fee	OW	APD

LC Tribal 5-25-46	25	040S	060W	4301352126	Indian	Indian	OW	APD
8-33D-35 BTR	33	030S	050W	4301352161	Indian	Fee	OW	APD
5-4D-36 BTR	4	030S	060W	4301352175	Indian	Fee	OW	APD
'-4D-36 BTR	4	030S	060W	4301352176	Indian	Fee	OW	APD
C Tribal 4-36D-47	36	040S	070W	4301352186	Indian	Indian	OW	APD
.C Tribal 4-22D-46	22	040S	060W	4301352944	Indian	Indian	OW	APD
.C Tribal 16-22D-46	22	040S	060W	4301352945	Indian	Indian	OW	APD
.C Tribal 11-19D-46	19	040S	060W	4301352946	Indian	Indian	OW	APD
.C Tribal 7-20D-45	20	040S	050W	4301352947	Indian	Indian	OW	APD
5-11D-35 BTR	11	030S	050W	4301353056	Indian	Fee	OW	APD
3-11D-35 BTR	11	030S	050W	4301353057	Indian	Fee	OW	APD
3TR 16-36D-37	36	030S	070W	4301353059	Indian	Fee	OW	APD
I-29D-35 BTR	30	030S	050W	4301353060	Indian	Fee	ow	APD
-30D-35 BTR	30	030S	050W	4301353061	Fee	Fee	OW	APD
C TRIBAL 3-23D-46	23	040S	060W	4301353066	Indian	State	ow	APD
C Tribal 14-23D-46	23	040S	060W	4301353067	Indian	State	OW	APD
.C Tribal 13-25D-46	25	040S	060W	4301353068	Indian	Indian	OW	APD
C Tribal 14-26D-46	26	040S	060W	4301353069	Indian	State	OW	APD
C Tribal 5-26D-46	26	040S	060W	4301353070	Indian	State	OW	APD
C Tribal 11-35D-45	35	040S	050W	4301353071	Indian	State	OW	APD
C Tribal 7-35D-45	35	040S	050W	4301353072	Indian	State	OW	APD
C Tribal 3-35D-45	35	040S	050W	4301353075	Indian	State	OW	APD
C Tribal 14-36D-45	36	040S	050W	4301353076	Indian	State	OW	APD
C Tribal 13-36D-45	36	040S	050W	4301353077	Indian	State	OW	APD
C Tribal 10-36D-45	36	040S	050W	4301353078	Indian	State	OW	APD
.C Tribal 8-36D-45	36	040S	050W	4301353079	Indian	State	OW	APD
.C Tribal 6-36D-45	36	040S	050W	4301353080	Indian	State	OW	APD
.C Tribal 1-34D-46	34	040S	060W	4301353081	Indian	State	OW	APD
.C Tribal 9-27D-46	27	040S	060W	4301353082	Indian	State	OW	APD
.C Tribal 13-35D-45	35	040S	050W	4301353083	Indian	State	OW	APD
C Tribal 8-35D-45	35	040S	050W	4301353084	Indian	State	OW	APD
.C Tribal 15-35D-45	35	040S	050W	4301353085	Indian	State	OW	APD
C Tribal 12-25D-45	25	040S	050W	4301353122	Indian	Indian	OW	APD
C Tribal 14-25D-45	25	040S	050W	4301353123	Indian	Indian	OW	APD
C Tribal 10-25D-45	25	040S	050W	4301353124	Indian	Indian	ow	APD
C Tribal 11-26-45	26	040S	050W	4301353125	Indian	Indian	OW	APD
C Tribal 13-26D-45	26	040S	050W	4301353126	Indian	Indian	OW	APD
C Tribal 7-31D-46	31	040S	060W	4301353127	Indian	Indian	OW	APD
.C Tribal 7-19D-45	19	040S	050W	4301353128	Indian	Indian	OW	APD
.C Tribal 5-19D-45	19	040S	050W	4301353130	Indian	Indian	OW	APD
.C Tribal 7-25D-46	25	040S	060W	4301353132	Indian	Indian	OW	APD

	15.	1							
_C Tribal 7-24D-46	24	0408	060W	4301353134		Indian	Indian	OW	APD
.C Tribal 14-31D-46	31	040S	060W	4301353135		Indian	Indian	OW	APD
C Tribal 14-30D-46	30	040S	060W	4301353136		Indian	Indian	OW	APD
13-4-35 BTR SWD	4	030S	050W	4301353293		Fee	Fee	OW	APD
.C FEE 14-26D-47	26	040S	070W	4301353294	1	Fee	Indian	OW	APD
C Fee 5-25D-47	25	040S	070W	4301353295		Fee	Indian	OW	APD
7-35-46 LC SWD	35	040S	060W	4301353296		Fee	Fee	OW	APD
.C Fee 1H-33-47	32	040S	070 W	4301353309		Fee	Indian	ow	APD
_C FEE 14-2D-58	2	050S	W080	4301353312		Fee	Indian	OW	APD
C FEE 13H-21-47	21	040S	070W	4301353313		Fee	Indian	OW	APD
C Fee 16-21D-47	21	040S	070W	4301353326		Fee	Indian	OW	APD
6-7D-46 BTR	7	040S	060W	4301353328		Fee	Indian	OW	APD
C Fee 15-26D-47	26	040S	070W	4301353331		Fee	Indian	OW	APD
.C Fee 4-24D-47	23	040S	070W	4301353332		Fee	Indian	OW	APD
.C Fee 5-34D-47	34	040S	070W	4301353333		Fee	Indian	OW	APD
.C Fee 5-35D-47	35	040S	070W	4301353334	:	Fee	Indian	OW	APD
3-34D-47 LC Fee	34	040S	070W	4301353337		Fee	Indian	OW	APD
4-35D-35 BTR	35	030S	050W	4301352120		Fee	Fee	ow	DRL
-17D-46 BTR	17	040S	060W	4301351078		Indian	Indian	OW	OPS
-34D-35 BTR	34	030S	050W	4301351187		Indian	Fee	OW	OPS
5-10D-45 BTR	10	040S	050W	4301351221		Indian	Indian	OW	OPS
-3D-45 BTR	3	040S	050W	4301351810		Indian	Indian	OW	OPS
-34D-35 BTR	34	030S	050W	4301352117		Fee	Fee	OW	OPS
-35D-35 BTR	35	030S	050W	4301352118		Fee	Fee	OW	OPS
-2D-46 BTR	2	040S	060W	4301353086		Indian	Fee	OW	OPS
'-21-46 DLB	21	040S	060W	4301333567	16526	Indian	Indian	OW	P
.C TRIBAL 1H-27-46	27	040S	060W	4301333568	18175	Indian	Fee	GW	P
'-29-46 DLB	29	040S	060W	4301333584	17603	Indian	Fee	GW	P
C TRIBAL 12H-28-46	28	0408	060W	4301333631	18132	Indian	Indian	GW	P
.C TRIBAL 13H-21-46	21	0408	060W	4301333632	18107	Indian	Indian	GW	 P
2-36-36 BTR	36	030S	060W	4301333638	16336	Indian	Fee	GW	P
i-5-46 BTR	5	0408	060W	4301333639	16542	Indian	Fee	OW	P
5-23-36 BTR	23	0308	060W	4301333642	16675	Indian	Fee	GW	P
4-29-36 BTR	29	0308	060W	4301333643	16725	Indian	Fee	ow	P
4-30-36 BTR	30	0308	060W	4301333644	16701	Indian	Fee	GW	<u>'</u>
'-20-46 DLB	20	040S	060W	4301333657	16584	Indian	Indian	OW	'P
.C TRIBAL 5-21D-46	21	0408	060W	4301333658	18887	Indian	Indian	OW	P
-20-46 DLB	20	0408	060W	4301333659	18750	Indian	Indian	GW	P
.C TRIBAL 13H-20-46	20	0408	060W	4301333678	17979	Indian	Indian	GW	P
14-7-46 BTR	7	0408	060W	4301333806	16890	Indian	Indian	GW	P
	1.	0.00	100011	TOO OOOOOO	10000	HIMIAII	HIGHAIL	UVV	1 1-1

1-5-45 BTR	5	040S	050W	4301333868	16931	Indian	Indian	OW	Р
5-16-36 BTR	16	030S	060W	4301333970	17195	Indian	Fee	ow	P
5-29-36 BTR	29	030S	060W	4301333972	17557	Indian	Fee	OW	P
4-30-36 BTR	30	030S	060W	4301333973	17249	Indian	Fee	OW	P
7-19-46 DLB	19	040S	060W	4301334004	19018	Indian	Indian	OW	Р
5-25-36 BTR	25	0308	060W	4301334021	17126	Fee	Fee	OW	Р
5-4-45 BTR	4	0408	050W	4301334089	17507	Indian	Indian	OW	Р
13-2-46 BTR	2	040S	060W	4301334090	18618	Indian	Indian	ow	Р
2-3-45 BTR	3	040S	050W	4301334099	17932	Indian	Indian	OW	Р
7-6-45 BTR	6	040S	050W	4301334100	17653	Indian	Indian	ow	Р
1-9-45 BTR	9	040S	050W	4301334101	17910	Indian	Indian	OW	P
8-10-45 BTR	10	040S	050W	4301334102	17530	Indian	Indian	OW	Р
7-17-45 BTR	17	040S	050W	4301334104	17933	Indian	Indian	OW	P
16-7-45 BTR	7	040S	050W	4301334111	17665	Indian	Indian	OW	Р
15-18-45 BTR	18	040S	050W	4301334112	17832	Indian	Indian	ow	P
6-12-46 BTR	12	040S	060W	4301334114	17964	Indian	Indian	ow	P
5-13-46 BTR	13	040S	060W	4301334115	17833	Indian	Indian	OW	P
16-26-36 BTR	26	030S	060W	4301334132	18028	Indian	Fee	OW	P
1-23-36 BTR	23	030S	060W	4301334136	17722	Indian	Fee	OW	P
15-10-36 BTR	10	030S	060W	4301334277	17419	Indian	Fee	OW	Р
14-5-46 BTR	5	040S	060W	4301350307	17624	Fee	Fee	OW	P
14X-22-46 DLB	22	040S	060W	4301350351	17604	Indian	Indian	OW	Р
16-13-36 BTR	13	030S	060W	4301350372	17853	Indian	Fee	ow	Р
5-33-46 DLB	33	040S	060W	4301350397	17765	Indian	Fee	OW	Р
5-34-46 DLB	34	040S	060W	4301350415	17801	Indian	State	GW	Р
LC FEE 12H-32-46	32	040S	060W	4301350431	18003	Fee	Fee	OW	P
1-13D-47 BTR	13	040S	070W	4301350445	18205	Indian	Fee	OW	Р
16-8D-45 BTR	8	040S	050W	4301350466	18799	Indian	Indian	OW	Р
7-13D-46 BTR	13	040S	060W	4301350470	18076	Indian	Indian	OW	Р
14-8D-45 BTR	8	040S	050W	4301350567	18207	Indian	Indian	ow	Р
14-5D-45 BTR	5	040S	050W	4301350568	18108	Indian	Indian	OW	Р
16-31D-36 BTR	31	030S	060W	4301350573	18004	Indian	Fee	ow	P
5-7D-46 BTR	7	040S	060W	4301350574	18176	Indian	Indian	OW	Р
LC TRIBAL 13H-33-46	34	040S	060W	4301350575	18223	Indian	State	OW	Р
5-8-45 BTR	8	040S	050W	4301350607	18279	Indian	Indian	OW	Р
16-6D-45 BTR	6	040S	050W	4301350610	18177	Indian	Indian	OW	P
5-18D-45 BTR	18	040S	050W	4301350611	18300	Indian	Indian	OW	Р
7-26-37 BTR	26	030\$	070W	4301350641	18131	Indian	Fee	OW	Р
3-11D-36 BTR	11	030S	060W	4301350642	18299	Indian	Fee	OW	Р
16-1D-46 BTR	1	040S	060W	4301350675	18525	Indian	Indian	ow	Р
14-3-45 BTR	3	040S	050W	4301350676	18363	Indian	Indian	ow	Р

4-17D-45 BTR	17	040S	050W	4301350687	18517	Indian	Indian	OW	Р
5-6D-45 BTR	6	040S	050W	4301350688	18726	Indian	Indian	OW	Р
7-7D-45 BTR	7	040S	050W	4301350689	18380	Indian	Indian	OW	Ρ
14-10D-45 BTR	10	040S	050W	4301350754	18447	Indian	Indian	OW	P
14-9D-45 BTR	9	040S	050W	4301350755	18379	Indian	Indian	OW	P
13-16D-36 BTR	16	030S	060W	4301350757	18206	Indian	State	OW	Р
5-9D-36 BTR	9	030S	060W	4301350843	18381	Indian	Fee	ow	P
16-5D-46 BTR	5	040S	060W	4301350844	18280	Fee	Fee	OW	Р
5-27D-37 BTR	27	030S	070W	4301350847	18526	Indian	Fee	OW	Р
7-4D-45 BTR	4	040S	050W	4301350884	18562	Indian	Indian	OW	Р
2-16D-45 BTR	16	040S	050W	4301350899	18619	Indian	Indian	OW	P
16-10D-45 BTR	10	040S	050W	4301350902	18725	Indian	Indian	OW	P
5-2D-36 BTR	2	030S	060W	4301350913	18886	Indian	Fee	OW	Р
13H-27-36 BTR	27	030S	060W	4301350918	18445	Indian	State	OW	P
8-16D-46 BTR	16	040S	060W	4301350953	19027	Indian	Indian	OW	Р
16-16D-46 BTR	16	040S	060W	4301350956	19028	Indian	Indian	OW	P
16-9D-45 BTR	9	040S	050W	4301350962	18662	Indian	Indian	OW	Р
14-31D-36 BTR	31	030S	060W	4301350973	18524	Indian	Fee	OW	Р
5-10D-36 BTR	10	030S	060W	4301350978	18989	Indian	Fee	OW	Р
1-32D-36 BTR	32	030S	060W	4301350979	18648	Indian	Fee	OW	Р
16-12D-36 BTR	12	030S	060W	4301350980	18748	Indian	Fee	ow	Р
2-18D-45 BTR	18	040S	050W	4301350991	18776	Indian	Indian	OW	P
3-1-46 BTR	1	040S	060W	4301351017	18777	Indian	Fee	ow	Р
10-5-45 BTR	5	040S	050W	4301351062	18724	Indian	Indian	OW	Р
12-4D-45 BTR	4	040S	050W	4301351063	18813	Indian	Indian	ow	Р
1-10D-45 BTR	10	040S	050W	4301351064	18966	Indian	Indian	ow	Р
16-2D-46 BTR	2	040S	060W	4301351079	18830	Indian	Indian	OW	Р
9H-4-45 BTR	4	040S	050W	4301351092	18814	Indian	Indian	OW	Р
12-17-45 BTR	17	040S	050W	4301351097	18984	Indian	Indian	OW	Р
5-9D-46 BTR	9	040S	060W	4301351109	19313	Indian	Fee	OW	Р
14-9D-36 BTR	9	030S	060W	4301351144	19004	Indian	Fee	OW	Р
5-31D-36 BTR	31	030S	060W	4301351146	18691	Indian	Fee	ow	Р
4-9D-45 BTR	9	040S	050W	4301351157	18883	Indian	Indian	OW	Р
8-12D-46 BTR	12	040S	060W	4301351159	18911	Indian	Indian	OW	Р
LC TRIBAL 16-23D-47	23	040S	070W	4301351180	18617	Indian	Indian	OW	Р
14-7D-45 BTR	7	040S	050W	4301351222	18949	Indian	Indian	OW	Р
5-16D-45 BTR	16	040S	050W	4301351223	18987	Indian	Indian	OW	P
4-5D-45 BTR	5	040S	050W	4301351242	18882	Indian	Indian	OW	P
LC TRIBAL 16H-19-45	19	040S	050W	4301351278	18627	Indian	Indian	OW	Р
LC TRIBAL 13-19D-45	19	040S	050W	4301351280	18628	Indian	Indian	OW	Р
LC TRIBAL 5-30D-45	30	040S	050W	4301351281	19448	Indian	Indian	ow	Р

LC TRIBAL 15-24D-46	24	040S	060W	4301351283	18626	Indian	Indian	OW	Р
LC TRIBAL 13H-24-46	19	040S	050W	4301351289	18629	Indian	Indian	ow	Р
7-16-47 BTR	16	040S	070W	4301351296	18950	Indian	Fee	ow	P
14-18D-45 BTR	18	040S	050W	4301351313	19005	Indian	Indian	ow	Р
LC TRIBAL 16-30D-46	30	040S	060W	4301351320	19006	Indian	Indian	ow	Р
LC TRIBAL 5-20D-45	20	040S	050W	4301351331	19449	Indian	Indian	ow	Р
11-8D-46 BTR	8	040S	060W	4301351336	19314	Indian	Indian	OW	Р
5-7D-45 BTR	7	040S	050W	4301351350	18951	Indian	Indian	ow	Р
7-5-35 BTR	5	030S	050W	4301351599	19078	Indian	Fee	OW	P
13-5D-35 BTR	5	030S	050W	4301351600	18996	Indian	Fee	ow	Р
11-5D-35 BTR	5	030S	050W	4301351601	19061	Fee	Fee	OW	Р
15-5D-35 BTR	5	030S	050W	4301351602	19062	Fee	Fee	OW	Р
9-5D-35 BTR	5	030S	050W	4301351609	19029	Indian	Fee	ow	Р
3-5D-35 BTR	5	030S	050W	4301351638	19079	Indian	Fee	OW	Р
7-8-46 BTR	8	040S	060W	4301351702	19315	Indian	Indian	ow	Р
7-30-46 DLB	30	040S	060W	4301351703	18997	Fee	Indian	OW	Р
3-13D-46 BTR	13	040S	060W	4301351718	18881	Indian	Indian	ow	Р
2-13D-46 BTR	13	040S	060W	4301351719	18885	Indian	Indian	OW	Р
12-12D-46 BTR	12	040S	060W	4301351720	18867	Indian	Indian	OW	P
10-12D-46 BTR	12	040S	060W	4301351721	18856	Indian	Indian	ow	Р
11-11D-47 BTR	11	040S	070W	4301352091	19633	Fee	Fee	ow	P
7-12D-47 BTR	12	040S	070W	4301352094	19600	Indian	Fee	ow	Р
5-12D-47 BTR	12	040S	070W	4301352095	19634	Indian	Fee	ow	Р
14-33D-35 BTR	33	030S	050W	4301352162	19450	Indian	Fee	ow	Р
16-33D-35 BTR	33	030S	050W	4301352163	19451	Indian	Fee	ow	Р
14-22-46 DLB	22	040S	060W	4301333660	17604	Indian	Indian	D	PA
13H-31-36 BTR	31	0308	060W	4301350465	18485	Indian	Fee	OW	PA
16X-23D-36 BTR	23	030S	060W	4301350623	18007	Indian	State	OW	PA
8-6-45 BTR	6	040S	050W	4301350900	18561	Indian	Indian	ow	PA
13-13-36 BTR	13	030S	060W	4301350919	18364	Indian	Fee	OW	PA
7-28-46 DLB	28	040S	060W	4301333569	16460	Indian	Indian	OW	S
5-21-36 BTR	21	030S	060W	4301333641	16674	Indian	Fee	GW	S
13-26-36 BTR	26	030S	060W	4301333980	17569	Indian	Fee	OW	S
14-1-46 BTR	1	040S	060W	4301334113	18516	Indian	Indian	OW	S
16-21-36 BTR	21	030S	060W	4301334130	17721	Indian	Fee	OW	S
14-21-36 BTR	21	030S	060W	4301334131	18006	Indian	Fee	OW	S
7-16-36 BTR	16	030\$	060W	4301334133	17834	Indian	Fee	OW	s
1-30-36 BTR	30	0308	060W	4301334134	17905	Indian	Fee	OW	S
16-30-36 BTR	30	0308	060W	4301334135	18005	Indian	Fee	OW	S
3-23-36 BTR	23	0308	060W	4301334137	17860	Indian	Fee	OW	S
16-16-36 BTR	16	0308	060W	4301334138	17666	Indian	Fee	OW	S

4-26-36 BTR	26	030S	060W	4301334139	17620	Fee	Fee	OW	S
9-11-36 BTR	11	030S	060W	4301334276	17451	Indian	Fee	OW	S
3-36-36 BTR	36	0308	060W	4301350398	17955	Indian	Fee	OW	S
7-10-36 BTR	10	030S	060W	4301350437	18052	Indian	Fee	OW	S
16-12D-46 BTR	12	040S	060W	4301350467	18051	Indian	Indian	OW	S
13H-13-46 BTR	13	040\$	060W	4301350468	18208	Indian	Indian	OW	S
13-12-46 BTR	12	040S	060W	4301350469	18233	Indian	Indian	OW	S
14-8D-36 BTR	8	030S	060W	4301350612	18163	Indian	Fee	OW	S
14-7D-36 BTR	7	030S	060W	4301350613	18330	Indian	Fee	OW	S
16-9-36 BTR	9	0308	060W	4301350645	18078	Indian	Fee	OW	S
7-27-37 BTR	27	030S	070W	4301350647	18090	Indian	Fee	OW	S
16-12D-37 BTR	12	030S	070W	4301350785	18446	Indian	Fee	OW	S
14-21D-37 BTR	21	030S	070W	4301350859	18548	Indian	Fee	OW	S
10-18D-36 BTR	18	030S	060W	4301350915	18884	Indian	Fee	OW	S
5-27D - 36	27	030S	060W	4301350917	18482	Indian	State	OW	S
10-36D-36 BTR	36	030S	060W	4301351005	18523	Indian	Fee	OW	S
14-6D-45 BTR	6	040S	050W	4301351158	18967	Indian	Indian	OW	S
5H-1-46 BTR UTELAND BUTTE	6	040S	050W	4301351215	18728	Indian	Indian	OW	S
5H-1-46 BTR WASATCH	6	040S	050W	4301351216	18727	Indian	Indian	OW	S
1-25D-36 BTR	25	030S	060W	4301351294	18798	Indian	Fee	OW	S
5-5D-35 BTR	5	030S	050W	4301351605	19055	Indian	Fee	OW	S
16-23-36 BTR	23	030S	060W	4301333971	17182	Indian	Fee	OW	TA
LC TRIBAL 14-23D-47	23	040S	070W	4301334022	18616	Indian	Indian	OW	TA
5-32D-36 BTR	32	030S	060W	4301350756	18328	Indian	Fee	OW	TA



October 20, 2016

RECEIVED

OCT 21 2016

Re: Bill Barrett Corporation Transfer to New Operator

DIV. OF OIL, GAS & MINING

Dear Ms. Medina:

Attached please find the change of operation Form 9, Form 5's and Request to Transfer APD formchanging the operator from Bill Barrett Corporation to RIG II, LLC, effective 11/1/2016. Badlands Energy – Utah, LLC will be a sub-operator.

New Operator Contact information:

RIG II, LLC 1582 West 2600 South Woods Cross, Utah 84087-0298 Telephone:(801) 683-4245 Fax:(801) 298-9889

Upon reviewing the attached, please contact myself with any questions at 303-312-8115.

Sincerely,

Bill Barrett Corporation

Brady Riley Permit Analyst

STATE OF UTAH FORM 9 **DEPARTMENT OF NATURAL RESOURCES** 5. LEASE DESIGNATION AND SERIAL NUMBER: DIVISION OF OIL, GAS AND MINING (see attached well list) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME: SUNDRY NOTICES AND REPORTS ON WELLS N/A 7, UNIT or CA AGREEMENT NAME: Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals. 1. TYPE OF WELL 8. WELL NAME and NUMBER OIL WELL 🔽 GAS WELL (see attached well list) 2. NAME OF OPERATOR: 9. API NUMBER RIG II, LLC 3. ADDRESS OF OPERATOR PHONE NUMBER: 10. FIELD AND POOL, OR WILDCAT: 1582 West 2600 South (801) 683-4245 STATE UT ZIP 84087 Wood Cross 4. LOCATION OF WELL FOOTAGES AT SURFACE: (see attached well list) COUNTY: QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: STATE: UTAH CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 11. TYPE OF SUBMISSION TYPE OF ACTION ACIDIZE REPERFORATE CURRENT FORMATION NOTICE OF INTENT (Submit in Duplicate) ALTER CASING FRACTURE TREAT SIDETRACK TO REPAIR WELL Approximate date work will start; CASING REPAIR **NEW CONSTRUCTION** TEMPORARILY ABANDON 11/1/2016 CHANGE TO PREVIOUS PLANS OPERATOR CHANGE TUBING REPAIR CHANGE TUBING PLUG AND ABANDON VENT OR FLARE SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK WATER DISPOSÁL (Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME) WATER SHUT-OFF Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE OTHER: CONVERT WELL TYPE **RECOMPLETE - DIFFERENT FORMATION** 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. RIG II, LLC IS SUBMITTING THIS SUNDRY AS NOTIFICATION THAT THE WELLS LISTED ON THE ATTACHED LIST HAVE BEEN SOLD TO-Rig II, LLC BY BILL BILL BARRETT CORPORATION EFFECTIVE 11/1/2016. PLEASE REFER ALL FUTURE CORRESPONDENCE TO THE ADDRESS BELOW. RIG II, LLC 1582 West 2600 South Woods Cross, Utah 84087-0298 801-683-4245 (STATE/FEE BOND # 9219529/ BLM BOND # UTB000712/ BIA BOND # LPM9224670) BILL BARRETT CORPORATION NOILS RIG II, LLC MAME (PLEASE PRINT) _ NAME (PLEASE PRINT) SIGNATURE SIGNATURE EH&S, Government and Regulatory Affairs Jesse McSwain Manager NAME (PLEASE PRINT) 1012016

APPROVED

NOV 0 7 2016

(This space for State use only)

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

Request to Transfer Application or Permit to Drill

	(This form should ac	ccompany a Sundr	y Notice, Form 9, reque	esting APD transfer)		
Well	name:	(See attached li	st)			
API ı	number:					
Loca	ation:	Qtr-Qtr:	Section:	Township: Range:		
Com	pany that filed original application:	Bill Barrett Corp	oration			
Date	original permit was issued:					
Com	pany that permit was issued to:	Bill Barrett Cor	poration			
Check one		Des	ired Action:			
	Transfer pending (unapproved) App					
	The undersigned as owner with legal r submitted in the pending Application for owner of the application accepts and a	or Permit to Dril	l, remains valid ar	nd does not require revision. The	new	
✓	Transfer approved Application for F	ermit to Drill t	o new operator			
	The undersigned as owner with legal r information as submitted in the previous revision.				re	
Folio	owing is a checklist of some items rel	ated to the ap	plication, which s	should be verified.	Yes	No
If loc	ated on private land, has the ownership	changed?			✓	
	if so, has the surface agreement been	updated?				✓
	e any wells been drilled in the vicinity of tirements for this location?	the proposed w	rell which would af	fect the spacing or siting		✓
	e there been any unit or other agreemen osed well?	ts put in place t	hat could affect th	e permitting or operation of this		✓
	there been any changes to the access osed location?	route including	ownership or righ	t-of-way, which could affect the		✓
Has t	the approved source of water for drilling	changed?				✓
	e there been any physical changes to the s from what was discussed at the onsite		on or access route	which will require a change in		✓
Is bo	nding still in place, which covers this pro	posed well? B	ond No. 9219529-UDOGM/U	JTB000712-BLM / LPM9224670-BIA	1	
shou nece	desired or necessary changes to either a ld be filed on a Sundry Notice, Form 9, o ssary supporting information as required	or amended Ap	plication for Permi			red,
	e (please print) Jesse McSwain		Title Manager	2110		
_	esenting (company name) RIG II, LLC		Date 10 0	<u> 114 </u>		
rtepi	cooming (company name)			· · · · · · · · · · · · · · · · · · ·		

The person signing this form must have legal authority to represent the company or individual(s) to be listed as the new operator on the Application for Permit to Drill.

STATE OF UTAHDEPARTMENT OF NATURAL RESOURCES

DIVISION OF OIL, GAS AND MINING

TRANSFER OF AUTHORITY TO INJECT								
Well Name and Number 6-32-36 BTR SWD		4-8'			API Number 4301350921			
Location of Well				DUQUENOE	Field or Unit Name CEDAR RIM			
Footage: 1628 FNL 1553 FWL QQ, Section, Township, Range: SENW	32	38	6W	County : DUCHENSE State : UTAH	Lease Designation and Number 20G0005608			

EFFECTIVE DATE OF TRANSFER: 11/1/2016

CURRENT OP	PERATOR	
Company:	BILL BARRETT CORPORATION	Name: Duane Zavadil
Address:	1099 18th Street Ste 2300	Signature: 2nCd
	city DENVER state CO zip 80202	Senior Vice President - Title: EH&S, Government and Regulatory Affairs
Phone:	(303) 293-9100	Date: 10 20 16
Comments	· · · · · · · · · · · · · · · · · · ·	

Company:	RIG II, LLC	Name: Jesse McSwain
Address:	1582 West 2600 South	Signature: Jene MG:
	city Wood Cross state UT zip 84087	Title: Manager
Phone:	(801) 683-4245	Date: 10 20 10
Comments		Date. 10 CO 10

(This space for State use only)

Transfer approved by:

Approval Date: ///3//L

Comments:

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

	TRANSFER OF AL	JTHORITY TO INJECT	Γ
Well Name and 16-6D-46 BT			API Number 4301350781
ocation of Well		:	Field or Unit Name
Footage: 02	200 FSL 0099 FEL	County : DUCHESNE	ALTAMONT Lease Designation and Number
QQ, Section, Township, Range: SESE 6 4S 6W		State: UTAH	20G0005608
	11/1/2016		
EFFECTIVE L	DATE OF TRANSFER: 11/1/2016		
CURRENT OP	PERATOR		
Company:	BILL BARRETT CORPORATION	Name: Duane	e Zavadil
Address:	1099 18th Street Ste 2300	Signature:	m Zinal
	city DENVER state CO zip 80202	SeniorV	ice President - Government and Regulatory Affairs
Phone:	(303) 293-9100	Date:	20/16
Comments:			
oommonto.	•		
NEW OPERAT			
VEW OF LINA	iok		
Company:	RIG II, LLC	Name: Jesse	McSwain ⁽
Address:	1582 West 2600 South	Signature:	Leve MG:
, , , , , , , , , , , , , , , , , , , ,	city Wood Cross state UT zip 84087	Title: Mana	
Phone:	(801) 683-4245	Date:	120/16
Comments:	:		
This space for S	state use only)	· ·	1
Transfer ap	oproved by:	Approval Date:	11/3/16
	Title: VIC		•

Comments:

STATE OF UTAH

DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

	TRANSFER OF AL	JTHORITY TO INJEC	Γ	
ell Name and SWD 9-36 B	TR		API Number 4301350646	
cation of Well			Field or Unit Name CEDAR RIM	
Footage: 0539 FSL 0704 FEL		County : DUCHESNE	Lease Designation and Number	
QQ, Section, Township, Range: SESE 9 3S 6W		State: UTAH	2OG0005608	
FFECTIVE	DATE OF TRANSFER: 11/1/2016			
URRENT OP	PERATOR			
	DV L DADDETT CODDODATION	_		
Company:	BILL BARRETT CORPORATION	Name: Duane	e Zavadil	
Address:	1099 18th Street Ste 2300	Signature: Senior V	rice President -	
	city DENVER state CO zip 80202	Title: EH&S, G	Government and Regulatory Affairs	
Phone:	(303) 293-9100	Date: <u>\</u>	2014	
Comments:				
EW OPERAT	FOR			
Company:	RIG II, LLC	Name: Jesse	McSwain	
Address:	1582 West 2600 South	Signature:	ENE MEG-	
	city Wood Cross state UT zip 84087	Title: Mana	ger	
Phone:	(801) 683-4245	Date:	20/16	
Comments:				
is space for S	tate use only)			
Transfer approved by:		Approval Date:	Approval Date:	
	Title:			
	This well was own	rived by USE.	PH.	
Comr	ments: This well was approved with	Il be required.		
	EPH approved to.			